

## AMPMODU | AMPMODU Headers

TE Internal #: 280388-2


PCB Mount Header, Vertical, Board-to-Board, 44 Position, 2.54 mm [.1 in] Centerline, Partially Shrouded, Gold, Through Hole - Solder,

AMPMODU Headers

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles



PCB Connector Assembly Type: PCB Mount Header

PCB Mount Orientation: Vertical
Connector System: Board-to-Board

Number of Positions: 44
Number of Rows: 2

## **Features**

## **Product Type Features**

PCB Connector Assembly Type	PCB Mount Header
Connector System	Board-to-Board
Header Type	Partially Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board

## **Configuration Features**

Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	44
Number of Rows	2

### **Electrical Characteristics**

Dielectric Withstanding Voltage (Max)	750 V	
---------------------------------------	-------	--

## **Body Features**

Connector Profile	Standard
Primary Product Color	Black

## **Contact Features**

PCB Contact Termination Area Plating Material Thickness	2.5 µm
Contact Shape & Form	Round



Contact Mating Area Plating Material Finish	Bright
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	.381 μm[15 μin]
Contact Type	Pin
Termination Features	
Termination Post & Tail Length	3.5 mm[.138 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Retention	With
Panel Mount Feature	Without
Mating Alignment	With
Mating Alignment Type	Polarization
PCB Mount Retention	Without
PCB Mount Alignment	Without
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	2.54 mm[.1 in]
Housing Material	Thermoplastic
Dimensions	
Row-to-Row Spacing	2.54 mm[.1 in]
Usage Conditions	
Housing Temperature Rating	Standard
	Standard -65 – 105 °C[-85 – 221 °F]
Housing Temperature Rating	
Housing Temperature Rating  Operating Temperature Range	
Housing Temperature Rating  Operating Temperature Range  Operation/Application	-65 – 105 °C[-85 – 221 °F]
Housing Temperature Rating  Operating Temperature Range  Operation/Application  Circuit Application	-65 – 105 °C[-85 – 221 °F]

# **Product Compliance**



#### For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Not Low Halogen - contains Br or Cl > 900 ppm.
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

## Compatible Parts







## Also in the Series | AMPMODU Headers






PCB Connector Mounting(1)



PCB Connector Shrouds(1)



PCB Headers & Receptacles(4875)



PCB Latches, Locks & Retainers(1)




Wire-to-Board Connector Assemblies & Housings(5)



Wire-to-Board Connector Contacts(65)

# Customers Also Bought



TE Part #2-1761606-6 IDC LOW PRO HDR 16P VERT LG LAT BLUE



8P MODU II SHRD HDR,RT ANG, 0.38



6P MODU II SHRD HDR, RT ANG, 0.38



2X4P AMPMODU II SHRD HDR,ST,0.38



4P MODU II SHRD HDR, RT ANG, 0.38



## **Documents**

## **Product Drawings**

2X22P MODU II SHRD HDR,ST, 0.38AU

English

### **CAD Files**

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_280388-2\_T\_c-280388-2-t.2d\_dxf.zip



English

**Customer View Model** 

ENG\_CVM\_CVM\_280388-2\_T\_c-280388-2-t.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_280388-2\_T\_c-280388-2-t.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Product Environmental Compliance

**TE Material Declaration** 

English