

## Accessories - ICC-MT 1,5-2,5 BA - 3190593

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Module male contact, is inserted into the ICC connector shell after the conductor has been crimped, for conductors from 1.5-2.5 mm<sup>2</sup>, ribbon contact

Supplied in tape form - please note the drawing.



### Key commercial data

Packing unit	1 pc
Minimum order quantity	4000 pc
Weight per Piece (excluding packing)	0.99 GRM
Custom tariff number	85369010
Country of origin	Germany

### Technical data

#### General

Nominal current	12 A
Conductor cross section stranded min.	1.5 mm <sup>2</sup>
Max. conductor cross section, stranded	2.5 mm <sup>2</sup>

#### Connection data

Core diameter including insulation	2.11 mm ... 3.1 mm
Stripping length of individual wires	4 mm

### Classifications

#### eCl@ss

eCl@ss 4.0	272607xx
eCl@ss 4.1	27260701
eCl@ss 5.0	27260701

## Accessories - ICC-MT 1,5-2,5 BA - 3190593

### Classifications

#### eCl@ss

eCl@ss 5.1	27260701
eCl@ss 6.0	27260704
eCl@ss 7.0	27440402
eCl@ss 8.0	27440402

#### ETIM

ETIM 3.0	EC001121
ETIM 4.0	EC001121
ETIM 5.0	EC002641

#### UNSPSC

UNSPSC 6.01	30211810
UNSPSC 7.0901	39121410
UNSPSC 11	39121409
UNSPSC 12.01	39121409
UNSPSC 13.2	39121409

### Approvals

#### Approvals

---

Approvals

GOST

---


Ex Approvals

---

Approvals submitted

---

Approval details

GOST 
--

### Drawings

## Accessories - ICC-MT 1,5-2,5 BA - 3190593

Dimensioned drawing

