



# EVQ4317-R-01A

## 45V, 7A, Low-I<sub>Q</sub>, Synchronous Step-Down Converter with Frequency Spread Spectrum Evaluation Board, AEC-Q100 Qualified

### DESCRIPTION

The EVQ4317-R-01A evaluation board is designed to demonstrate the capabilities of the MPQ4317, a synchronous, step-down switching regulator with a configurable frequency and integrated, internal high-side MOSFETs (HS-FET) and low-side MOSFETs (LS-FET). It provides up to 7A of highly efficient output current (I<sub>OUT</sub>), with current mode control for fast loop response.

The wide 3.3V to 45V input voltage (V<sub>IN</sub>) range accommodates a variety of step-down applications in automotive input environments. A 1.7μA quiescent current (I<sub>Q</sub>) in shutdown mode allows the device to be used in battery-powered applications. High power conversion

efficiency across a wide load range is achieved by scaling down the switching frequency (f<sub>SW</sub>) under light-load conditions to reduce the switching and gate driver losses.

Frequency foldback helps prevent inductor current runaway during start-up. Thermal shutdown provides reliable, fault-tolerant operation. A high duty cycle and low-dropout mode are provided for automotive cold crank conditions.


The EVQ4317-R-01A is fully assembled and tested. The MPQ4317 is available in a QFN-20 (4mmx4mm) wettable flank package, and is AEC-Q100 Grade 1 qualified.

### PERFORMANCE SUMMARY

Specifications are at T<sub>A</sub> = 25°C, unless otherwise noted.

Parameter	Condition	Value
Input voltage (V <sub>IN</sub> ) range		3.3V to 45V
Output voltage (V <sub>OUT</sub> )	V <sub>IN</sub> = 3.3V to 45V, I <sub>OUT</sub> = 0A to 7A	3.3V
Maximum output current (I <sub>OUT</sub> )	V <sub>IN</sub> = 3.3V to 45V	7A
Typical efficiency	V <sub>IN</sub> = 12V, V <sub>OUT</sub> = 3.3V, I <sub>OUT</sub> = 7A	88.8%
Switching frequency (f <sub>SW</sub> )		410kHz

### EVQ4317-R-01A EVALUATION BOARD



LxWxH (8.3cmx8.3cmx1.3cm)

Board Number	MPS IC Number
EVQ4317-R-01A	MPQ4317GRE-AEC1

## QUICK START GUIDE

1. Preset the power supply ( $V_{IN}$ ) between 3.3V and 45V. Electronic loads represent a negative impedance to the regulator, and setting a current too high can trigger hiccup mode.
2. Turn off the power supply. If longer cables (>0.5m total) are used between the source and the evaluation board, install a damping capacitor at the input terminals, especially if  $V_{IN} \geq 24V$ .
3. Connect the power supply terminals to (see Figure 2 on page 3):
  - a. Positive (+): VEMI
  - b. Negative (-): GND
4. Connect the load terminals to (see Figure 2 on page 3):
  - a. Positive (+): VOUT
  - b. Negative (-): GND
5. After making the connections, turn on the power supply. The board should automatically start up.
6. To use the enable function, apply a digital input to the EN pin. Drive EN above 1V to turn the regulator on; drive EN below 0.85V to turn the regulator off.
7. The MPQ4317's switching frequency ( $f_{SW}$ ) can be configured by R3, the FREQ pin's resistor ( $R_{FREQ}$ ). R3 can be estimated based on the relationship between  $f_{SW}$  and  $R_{FREQ}$  (see Figure 1).




Figure 1:  $f_{SW}$  vs.  $R_{FREQ}$

8. To use the sync function, apply a 350kHz to 1000kHz external clock to the SYNCIN pin to synchronize the internal clock's rising edge.
9. The output voltage ( $V_{OUT}$ ) is set by the external resistor divider. If  $R7 = 100k\Omega$ , then  $R8$  can be calculated with Equation (1):

$$R8 = \frac{R7}{\frac{V_{OUT}}{0.815V} - 1} \quad (1)$$

Table 1 shows the recommended R7 and R8 values for common output voltages.

Table 1: Resistor Selection for Output Voltages

$V_{OUT}$ (V)	R7 (k $\Omega$ )	R8 (k $\Omega$ )
3.3	100 (1%)	32.4 (1%)
5	100 (1%)	19.1 (1%)

Figure 2 shows the measurement equipment set-up.




Figure 2: Measurement Equipment Set-Up

## EVALUATION BOARD SCHEMATIC





Figure 3: Evaluation Board Schematic

## PACKAGE REFERENCE



**EVQ4317-R-01A BILL OF MATERIALS**

Qty	Ref	Value	Description	Package	Manufacturer	Manufacturer PN
3	CIN1, COUT2, COUT4	1nF	Ceramic capacitor, 50V, X7R	0603	Murata	GRM216R71H102KA01
3	CIN2, COUT1, COUT3	10nF	Ceramic capacitor, 50V, X7R	0603	Murata	GRM188R71H103KA01D
2	CIN3, CIN4	1 $\mu$ F	Ceramic capacitor, 50V, X7R	1206	TDK	C3216X7R1H105K
1	CIN5	47 $\mu$ F	Aluminum capacitor, 63V	SMD	Panasonic	EEHZA1J470P
2	C1A, C1B	10 $\mu$ F	Ceramic capacitor, 50V, X7R	1210	Murata	GRM32ER71H106KA12L
2	C1C, C1D	0.1 $\mu$ F	Ceramic capacitor, 50V, X7R	0603	Murata	GCJ188R71H104KA12D
2	C2A, C2B	47 $\mu$ F	Ceramic capacitor, 10V, X5R	1210	Murata	GRM32ER61A476KE20L
1	C3	22nF	Ceramic capacitor, 25V, X7R	0603	Murata	GRM188R71E223JA01D
1	C4	0.1 $\mu$ F	Ceramic capacitor, 50V, X7R	0603	Murata	GRM188R71H104KA93D
1	C5	47pF	Ceramic capacitor, 50V, C0G	0603	TDK	C1608C0G1H470J
1	C6	4.7 $\mu$ F	Ceramic capacitor, 10V, X5R	0603	Murata	GRM188R61A475KE15D
1	L1	10m $\Omega$	Magnetic bead, 6A	0805	TDK	MPZ2012S300AT000
1	L2	4.7 $\mu$ H	Inductor, 31.5m, 6A	SMD	Cyntec	VCMT063T-4R7MN5T
1	L3	4.7 $\mu$ H	Inductor, 15.02m $\Omega$ , 12.1A	SMD	Coilcraft	XAL6060-472MEC
3	R1, R7, R9	100k $\Omega$	Film resistor, 1%	0603	Yageo	RC0603FR-07100KL
1	R3	75k $\Omega$	Film resistor, 1%	0603	Yageo	RC0603FR-0775KL
1	R4	51k $\Omega$	Film resistor, 1%	0603	Yageo	RC0603FR-0751KL
1	R6	0 $\Omega$	Film resistor, 1%	0603	Yageo	RC0603FR-070RL
1	R8	32.4k $\Omega$	Film resistor, 1%	0603	Yageo	RC0603FR-0732K4L
4	C2C, C2D, R2, R5	NS				
1	JP1	2.54mm	Test pin, 3-pin	DIP	Any	
4	VEMI, GND, VOUT, GND	2mm	Golden pin	DIP	Custom <sup>(1)</sup>	
7	SYNCIN, ICS, PG, SYNCO, EN, GND, GND	1mm	Golden pin	DIP	Custom <sup>(1)</sup>	
1	U1	MPQ4317	45V, 7A, step-down converter, AEC-Q100	QFN-20 (4mmx4mm)	MPS	MPQ4317GRE-AEC1

**Note:**


1) Contact an MPS FAE for more information regarding custom pins.

## EVB TEST RESULTS

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### Input Current vs. Load Current

AAM mode,  $V_{OUT} = 3.3V$




### Input Current vs. Load Current

AAM mode,  $V_{OUT} = 5V$




### Efficiency vs. Load Current

AAM mode,  $V_{OUT} = 3.3V$ , 0.1mA to 10mA




### Efficiency vs. Load Current

AAM mode,  $V_{OUT} = 3.3V$ , 10mA to 1000mA




### Efficiency vs. Load Current

AAM mode,  $V_{OUT} = 3.3V$ , 1A to 7A



### Efficiency vs. Load Current

FCCM,  $V_{OUT} = 3.3V$ , 0.1mA to 10mA




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### Efficiency vs. Load Current

FCCM,  $V_{OUT} = 3.3V$ , 10mA to 1000mA




### Efficiency vs. Load Current

FCCM,  $V_{OUT} = 3.3V$ , 1A to 7A




### Efficiency vs. Load Current

AAM mode,  $V_{OUT} = 5V$ , 0.1mA to 10mA




### Efficiency vs. Load Current

AAM mode,  $V_{OUT} = 5V$ , 10mA to 1000mA




### Efficiency vs. Load Current

AAM mode,  $V_{OUT} = 5V$ , 1A to 7A



### Efficiency vs. Load Current

FCCM,  $V_{OUT} = 5V$ , 0.1mA to 10mA




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### Efficiency vs. Load Current

FCCM,  $V_{OUT} = 5V$ , 10mA to 1000mA




### Efficiency vs. Load Current

FCCM,  $V_{OUT} = 5V$ , 1A to 7A




### Load Regulation

AAM mode,  $V_{OUT} = 3.3V$




### Load Regulation

FCCM,  $V_{OUT} = 3.3V$




### Line Regulation

AAM mode,  $V_{OUT} = 3.3V$



### Line Regulation







FCCM,  $V_{OUT} = 3.3V$







## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.



## EVB TEST RESULTS *(continued)*

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### CISPR25 Class 5 Peak Conducted Emissions

150kHz to 108MHz




### CISPR25 Class 5 Average Conducted Emissions

150kHz to 108MHz




### CISPR25 Class 5 Peak Radiated Emissions

150kHz to 30MHz




### CISPR25 Class 5 Average Radiated Emissions

150kHz to 30MHz




### CISPR25 Class 5 Peak Radiated Emissions

Horizontal, 30MHz to 1GHz



### CISPR25 Class 5 Average Radiated Emissions

Horizontal, 30MHz to 1GHz




## EVB TEST RESULTS *(continued)*

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### CISPR25 Class 5 Peak Radiated Emissions

Vertical, 30MHz to 1GHz



### CISPR25 Class 5 Average Radiated Emissions

Vertical, 30MHz to 1GHz




## EVB TEST RESULTS *(continued)*

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{sw} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### Steady State

$I_{OUT} = 0A$ , AAM mode




### Steady State

$I_{OUT} = 0A$ , FCCM




### Steady State

$I_{OUT} = 7A$




### Start-Up through VIN

$I_{OUT} = 0A$ , AAM mode




### Start-Up through VIN

$I_{OUT} = 0A$ , FCCM



### Start-Up through VIN

$I_{OUT} = 7A$




## EVB TEST RESULTS *(continued)*

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{sw} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### Shutdown through VIN

$I_{OUT} = 0A$ , AAM mode




### Shutdown through VIN

$I_{OUT} = 0A$ , FCCM




### Shutdown through VIN

$I_{OUT} = 7A$




### Start-Up through EN

$I_{OUT} = 0A$ , AAM mode




### Start-Up through EN

$I_{OUT} = 0A$ , FCCM



### Start-Up through EN

$I_{OUT} = 7A$




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{sw} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### Shutdown through EN

$I_{OUT} = 0A$ , AAM mode




### Shutdown through EN

$I_{OUT} = 0A$ , FCCM




### Shutdown through EN

$I_{OUT} = 7A$




### SCP Entry

$I_{OUT} = 0A$ , AAM mode




### SCP Entry

$I_{OUT} = 0A$ , FCCM



### SCP Entry

$I_{OUT} = 7A$




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{sw} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### SCP Recovery

$I_{OUT} = 0A$ , AAM mode




### SCP Recovery

$I_{OUT} = 0A$ , FCCM




### SCP Recovery

$I_{OUT} = 7A$




### SCP Steady State




### Load Transient

$I_{OUT} = 3.5A$  to  $7A$ ,  $1.6A/\mu s$



### SYNC Operation

$I_{OUT} = 7A$ , SYNC frequency = 350kHz






## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{sw} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### SYNC Operation

$I_{OUT} = 7A$ , SYNC frequency = 530kHz




### SYNCO Operation

$I_{OUT} = 7A$ , SYNC frequency = 350kHz




### SYNCO Operation

$I_{OUT} = 7A$ , SYNC frequency = 530kHz




### PG in Start-Up through VIN

$I_{OUT} = 0A$




### PG in Start-Up through VIN

$I_{OUT} = 7A$



### PG in Shutdown through VIN

$I_{OUT} = 0A$




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### PG in Shutdown through VIN

$I_{OUT} = 7A$




### PG in Start-Up through EN

$I_{OUT} = 0A$




### PG in Start-Up through EN

$I_{OUT} = 7A$




### PG in Shutdown through EN

$I_{OUT} = 0A$




### PG in Shutdown through EN

$I_{OUT} = 7A$



### Low-Dropout Mode

$V_{IN} = 3.3V$ ,  $V_{OUT}$  set to 3.3V,  $I_{OUT} = 0A$




## EVB TEST RESULTS (continued)

Performance curves and waveforms are tested on the evaluation board,  $V_{IN} = 12V$ ,  $V_{OUT} = 3.3V$ ,  $C_{OUT} = 2 \times 47\mu F$ ,  $L = 4.7\mu H$ ,  $f_{SW} = 410kHz$ ,  $T_A = 25^\circ C$ , unless otherwise noted.


### Low-Dropout Mode

$V_{IN} = 3.3V$ ,  $V_{OUT}$  set to 3.3V,  $I_{OUT} = 7A$




### Load Dump

$V_{IN} = 12V$  to 36V,  $I_{OUT} = 7A$




### Cold Crank

$V_{IN} = 12V$  to 3.3V to 5V,  $I_{OUT} = 7A$




### $V_{IN}$ Ramping Up and Down

$I_{OUT} = 0.1A$



### $V_{IN}$ Ramping Down and Up

$I_{OUT} = 1mA$



PCB LAYOUT (2)




Figure 4: Top Silk and Top Layer




Figure 5: Mid-Layer 1




Figure 6: Mid-Layer 2




Figure 7: Bottom Layer and Bottom Silk

Note:

- 2) The copper thickness is 2oz.



## REVISION HISTORY

Revision #	Revision Date	Description	Pages Updated
1.0	4/22/2022	Initial Release	-

**Notice:** The information in this document is subject to change without notice. Please contact MPS for current specifications. Users should warrant and guarantee that third-party Intellectual Property rights are not infringed upon when integrating MPS products into any application. MPS will not assume any legal responsibility for any said applications.