



Notes:

1. Electrical Specifications:
 - Meets USB 2.0 Specification
 - Contact Resistance: 30 mOhm max.
 - Insulation Resistance: 1000 MOhm min. @ 100 VDC
 - Current Rating: 1.5 A max. at 25°C
 - Working Voltage: 30 V (RMS) max.
 - DWV: 500 VAC/60s at sea Level
 - Operating Temperature: -40°C to +85°C

2. Material and Finish:

- Coupling Ring: Zinc Die-Cast, Nickel Plated
- USB Plug Housing: ABS, Nickel Plated, UL94 V-0
- Interfacial Seal: Silicon, Color: White
- Cable Fitting: Brass, Nickel Plated, UL94 V-0
- Cable Fitting Rubber Ring: NBR, Color: Black
- USB Metal Shell: SPCC, Nickel Plated
- USB Insulator: PBT, UL94 V-0, White
- USB Contacts: Copper Alloy,
- USB Contact Finish: 30 u" Gold min. over Nickel for mating area, Tin over Nickel for solder cup

3. USB Type A Plug accepts AWG28 to AWG24 wires, Cable OD of 4.0 mm to 5.5 mm

4. IP67 rated when fully mated with the appropriate mating connector

RoHS Compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY MANNER AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC CORPORATION.	Customer:			Tolerance Unless otherwise specified			Scale: 1.5:1	Dim. in mm		
	Name	Title	Approval Date	0 PLC ±0.50	1 PLC ±0.38		Material: See Notes Title: Die-Cast IP67 USB Plug Kit with USB 2.0 Type A Plug (Solder Cup) Nickel Plated Zinc Die-Cast Version	DIN A3 Sheet 1/1		
	f	1 x f	Sep/08/2017	Vincent Ke	2 PLC ±0.25	2010			Date	Name
	e	1 x e	Apr/21/2017	Vincent Ke	3 PLC ±0.10	Draw.			Mar. 16	Vincent Ke
d	1 x d	Apr/21/2017	Vincent Ke	ANGLES ±3	Appd.	Mar. 16	J. Chaudry			
c	1 x c	Jun/23/1024	Vincent Ke		Norm					
b	1 x b	Jan/28/2011	Vincent Ke		D-old					
a	original									
Rev.	Changes	Date	Name			Drawing No.: 17K1A154 Part No.: 17-200591				