

## Han 1A-2+PE-s-m latch



Image is for illustration purposes only. Please refer to product description.

Part number	09 10 002 2600
Specification	Han 1A-2+PE-s-m latch
HARTING eCatalogue	<a href="https://b2b.harting.com/09100022600">https://b2b.harting.com/09100022600</a>

### Identification

Category	Inserts
Series	Han <sup>®</sup> 1A

### Version

Termination method	Screw termination
Gender	Male
Locking type	Snap-in latches
Size	1 A
Number of contacts	2
PE contact	Yes
Details	Order separately the single wire seal or the hoods/housings for an IP65 performance.

#### Details

A Han<sup>®</sup> 1A configuration that only consists of inserts (with or without strain relief, 09 10 000 5300) is an unenclosed connector. In this case protection against electric shock must be provided by the installation methods of the user.

Contact inserts must not be coupled or decoupled under electrical load.

Contact inserts must not be powered-up in the un-mated condition.

### Technical characteristics

Conductor cross-section	0.75 ... 1.5 mm <sup>2</sup>
Rated current	10 A
Rated voltage conductor-earth	230 V
Rated voltage conductor-conductor	400 V
Rated impulse voltage	4 kV
Pollution degree	3



## Technical characteristics

Insulation resistance	>10 <sup>8</sup> Ω
Tightening torque	0.25 Nm
Limiting temperature	-30 ... +90 °C
Mating cycles	≥100
Degree of protection acc. to IEC 60529	IP20

## Material properties

Material (insert)	Polyamide (PA)
Colour (insert)	RAL 9005 (jet black)
Material (contacts)	Copper alloy
Surface (contacts)	Silver plated
Material flammability class acc. to UL 94	V-0
RoHS	compliant with exemption
RoHS exemptions	6(c): Copper alloy containing up to 4 % lead by weight
ELV status	compliant with exemption
China RoHS	50
REACH Annex XVII substances	No
REACH ANNEX XIV substances	No
REACH SVHC substances	Yes
REACH SVHC substances	Lead

## Specifications and approvals

Specifications	EN 45545-2 R22: HL1, HL2, HL3
	EN 45545-2 R23: HL1, HL2, HL3
	EN 45545-2 R24: HL1, HL2, HL3
	IEC 61373 Category 1 Class B
	EN 60664-1
Approvals	DNV GL

## Commercial data

Packaging size	1
Net weight	10.1 g
Country of origin	Germany
European customs tariff number	85366990

Product data sheet  
09 10 002 2600  
Han 1A-2+PE-s-m latch

This product is not orderable anymore. Contact your local distribution partner for alternatives.



Pushing Performance

## Commercial data

eCl@ss

27440205 Contact insert for industrial connectors