

Cable kit , Riser Cards & I/O modules

PCM-10586-9562E

Installation Wiring Kit for PCM-9562

| Part No. | Cable Description | Quantity | PCM-9562 Connector | Terminating Connector |
|------------|-------------------|----------|------------------------|--|
| 1700160160 | Audio cable | 1 | CN4 | Cable 16-Pin (2.0 mm) Audio 16 cm |
| 1700002142 | Ethernet cable | 2 | CN10, CN12 | Ethernet Cable IDC10P 2.0 mm/RJ45 15cm |
| 1700260250 | LPT port cable | 1 | CN15 | Cable 25 cm 25P to 26P ASS'Y LPT Port 2.0 mm |
| 1700019109 | COM 4/5 cable | 1 | CN42 | A Cable 2 x 5P-2.0/D-SUB(M) 9P+D-SUB(M) 9P 25 cm |
| 1703100260 | USB Port cable | 4 | CN20, CN21, CN28, CN29 | Wire 10P 26 cm 2.0 mm For USB 2 PORT |
| 1703060191 | PS2 KB/MS Cable | 1 | CN25 | Cable 6P-2.0 mm Housing/6P (PS/2)/6P (K/B) 19 cm |
| 1700008941 | SATA Cable | 3 | CN32, CN33, CN34 | Cable 7P/7P SATA L=30cm Lock |
| 1700001296 | VGA cable | 1 | CN8 | VGA Cable D-SUB 3 x 5P(F)/2x 8P-2.0 15 cm |
| 1700100250 | COM1/2/3 | 3 | CN39, CN40, CN41 | F Cable IDE#2 10P-2.0/D-SUB 9P(M) 25 cm |
| 1703150102 | SATA Power Cable | 3 | None | SATA Power cable L= 10 cm |
| 170304015K | AT power cable | 1 | CN5 | A Cable 2 x 2P-4.2/B4P-5.08 x 2 15 cm |

Ordering Information

| | |
|-----------------|--------------------|
| PCM-10586-9562E | PCM-9562 cable kit |
|-----------------|--------------------|

PCI Riser Card



PCM-110

1-Slot PCI Riser Card for 5.25" Biscuit SBCs

CE FCC

Fits in PCM-95XX series
Provides bracket to secure Biscuit SBCs
Size: 103.7 x 56 mm (4.08" x 2.2")

Ordering Information

| P/N | Description |
|---------------|--|
| PCM-110-00A3E | 1-slot PCI riser Card for Biscuit SBCs |



PCM-261

LVDS/TTL to DVI Module

Supports 18 and 24-bit LVDS to DVI
Supports 18 or 24-bit TTL LCD to DVI (optional)

Specifications

| General | |
|------------------------------|--|
| Chipset | Silicon Image Sil 164; NS DS90CF364 |
| LCD Connector | Hirose Output Connector; DVI |
| Mechanical and Environmental | |
| Dimensions (L x W) | 72 x 62 mm |
| Weight | 0.029 kg (0.064 lb) |
| Operating Temperature | 0 ~ 60° C (32 ~ 140° F) |
| Operating Humidity | 0% ~ 90% relative humidity, non-condensing |
| Power | |
| Power Supply Voltage | +5 V, ±5% |

Ordering Information

| Standard | |
|----------------|---------------------------|
| PCM-261L-A0A1E | 24-bit LVDS to DVI Module |
| PCM-261L-B0A1E | 18-bit LVDS to DVI Module |
| PCM-261T-A0A1E | 24-bit TTL to DVI Module |

Packing List

| |
|-------------------|
| 1 x User manual |
| 1 x PCM-261 board |