



Main Product Characteristics

$V_{(BR)DSS}$	100V
$R_{DS(ON)}$	120mΩ
I_D	4A



SOT-223



Schematic Diagram

Features and Benefits

- Advanced MOSFET process technology
- Ideal for high efficiency switched mode power supplies
- Low on-resistance with low gate charge
- Fast switching and reverse body recovery




Description

The SSFL0956 utilizes the latest techniques to achieve high cell density and low on-resistance. These features make this device extremely efficient and reliable for use in high efficiency switch mode power supply and a wide variety of other applications.

Absolute Maximum Ratings ($T_C=25^{\circ}C$ unless otherwise specified)

Parameter	Symbol	Max.	Unit
Drain-Source Voltage	V_{DS}	100	V
Gate-Source Voltage	V_{GS}	±20	V
Drain Current-Continuous ($T_C=25^{\circ}C$)	I_D	4	A
Drain Current-Continuous ($T_C=100^{\circ}C$)		2.6	
Drain Current-Pulsed ¹	I_{DM}	16	A
Power Dissipation ($T_C=25^{\circ}C$)	P_D	5.2	W
Power Dissipation-De-rate above 25°C		0.042	
Thermal Resistance, Junction-to-Ambient	$R_{\theta JA}$	70	°C/W
Thermal Resistance, Junction-to-Case	$R_{\theta JC}$	24	°C/W
Operating Junction Temperature Range	T_J	-50 To +150	°C
Storage Temperature Range	T_{STG}	-50 To +150	°C


Electrical Characteristics ($T_J=25^\circ\text{C}$ unless otherwise specified)

Parameter	Symbol	Conditions	Min.	Typ.	Max.	Unit
On/Off Characteristics						
Drain-Source Breakdown Voltage	BV_{DSS}	$V_{GS}=0V, I_D=250\mu A$	100	-	-	V
BV_{DSS} Temperature Coefficient	$\Delta BV_{DSS}/\Delta T_J$	Reference to 25°C , $I_D=1mA$	-	0.09	-	$V/^\circ\text{C}$
Drain-Source Leakage Current	I_{DSS}	$V_{DS}=100V, V_{GS}=0V,$ $T_J=25^\circ\text{C}$	-	-	1	μA
		$V_{DS}=80V, V_{GS}=0V,$ $T_J=125^\circ\text{C}$	-	-	10	μA
Gate-Source Leakage Current	I_{GSS}	$V_{GS}=\pm 20V, V_{DS}=0V$	-	-	± 100	nA
Static Drain-Source On-Resistance	$R_{DS(ON)}$	$V_{GS}=10V, I_D=4A$	-	-	120	m Ω
		$V_{GS}=4.5V, I_D=2A$	-	-	130	
Gate Threshold Voltage	$V_{GS(th)}$	$V_{GS}=V_{DS}, I_D=250\mu A$	1.2	1.6	2.5	V
$V_{GS(th)}$ Temperature Coefficient	$\Delta V_{GS(th)}$		-	-5	-	mV/ $^\circ\text{C}$
Forward Transconductance	g_{fs}	$V_{DS}=10V, I_D=2A$	-	8.7	-	S
Dynamic and Switching Characteristics						
Total Gate Charge ^{2,3}	Q_g	$V_{DS}=50V, I_D=2A,$ $V_{GS}=10V$	-	20	40	nC
Gate-Source Charge ^{2,3}	Q_{gs}		-	3.2	6	
Gate-Drain Charge ^{2,3}	Q_{gd}		-	3.6	7	
Turn-On Delay Time ^{2,3}	$t_{d(on)}$	$V_{DD}=50V, R_G=3.3\Omega,$ $V_{GS}=10V, I_D=1A$	-	18	36	nS
Rise Time ^{2,3}	t_r		-	4	8	
Turn-Off Delay Time ^{2,3}	$t_{d(off)}$		-	40	80	
Fall Time ^{2,3}	t_f		-	3	6	
Input Capacitance	C_{iss}	$V_{DS}=25V, V_{GS}=0V,$ $F=1MHz$	-	1400	2800	pF
Output Capacitance	C_{oss}		-	60	120	
Reverse Transfer Capacitance	C_{rss}		-	35	70	
Gate Resistance	R_g	$V_{GS}=0V, V_{DS}=0V,$ $F=1MHz$	-	2	4	Ω
Drain-Source Diode Characteristics and Maximum Ratings						
Continuous Source Current	I_S	$V_G=V_D=0V,$ Force Current	-	-	4	A
Pulsed Source Current	I_{SM}		-	-	8	A
Diode Forward Voltage	V_{SD}	$V_{GS}=0V, I_S=1A,$ $T_J=25^\circ\text{C}$	-	-	1	V

Note:

1. Repetitive rating: Pulsed width limited by maximum junction temperature.
2. Pulse test: pulse width $\leq 300\mu s$, duty cycle $\leq 2\%$.
3. Essentially independent of operating temperature.

Typical Electrical and Thermal Characteristic Curves




Figure 1. Continuous Drain Current vs. T_c




Figure 2. Normalized $R_{DS(ON)}$ vs. T_J




Figure 3. Normalized V_{th} vs. T_J




Figure 4. Gate Charge Waveform




Figure 5. Normalized Transient Impedance




Figure 6. Maximum Safe Operation Area

Typical Electrical and Thermal Characteristic Curves




Figure 7. Switching Time Waveform





Figure 8. EAS Waveform

Package Outline Dimensions

SOT-223



Symbol	Dimensions in Millimeters		Dimensions in Inches	
	Min	Max	Min	Max
A	1.52	1.8	0.06	0.071
A1	0	0.1	0	0.004
A2	1.5	1.7	0.059	0.067
b	0.66	0.82	0.026	0.032
c	0.25	0.35	0.01	0.014
D	6.2	6.4	0.244	0.252
D1	2.9	3.1	0.114	0.122
E	3.3	3.7	0.13	0.146
E1	6.83	7.07	0.269	0.278
e	2.300 (BSC)		0.091 (BSC)	
e1	4.5	4.7	0.177	0.185
L	0.9	1.15	0.035	0.045
θ	0°	10°	0°	10°