

VIEW ON TERMINATION SIDE

∞	Y	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	B	Y
◁	Z	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	A	Z

- A = 28 STANDARD CONTACTS L=3
- B = 28 STANDARD CONTACTS L=3
- Z = 4 FMLB CONTACTS ∅.6 L=3
- Y = 4 FMLB CONTACTS ∅.6 L=3
- S = 64 TOTAL NUMBER OF CONTACTS

Marking	Standard
Performance level	G2/0 = Contact area level2 / Termination tin
Flux proof	no
Fixing clip	no
Dimensions	SDA-85001-0001 sht.1
Technical Data	PS-85003-0001

Y	G2/0	b1,2,31,32,
Z	G2/0	a1,2,31,32
B	G2/0	b3-30
A	G2/0	a3-30
Contact symbol	Perform. level	Contact position number

C	LTR	REVISIONS	FOR PREVIOUS REVISIONS SEE MRI LIST
		see ECN No. 2204	96/07/18 Cd

UNLESS OTHERWISE SPECIFIED TOLERANCES: ANGULAR ± 2°		DRWG BY	SIGN
3 PLACE	± .	Cd	
2 PLACE	± .	CHK'D BY	SIGN
1 PLACE	± .	KN	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		APP'D BY	SIGN
DESIGN DIMENSION	<input type="checkbox"/> MM <input type="checkbox"/> IN.	SCALE	
EQUIVALENT DIMENSION	<input type="checkbox"/> MM <input type="checkbox"/> IN.		
IF TWO DIMENSIONS ARE SHOWN, THE UPPER IS THE DESIGN DIMENSION, LOWER IS SECONDARY			

REVISE ONLY ON CAD SYSTEM	SH. REV.	CAD/CAM PROJECT NAME	THIS DRAWING CONTAINS PROPRIETARY TO MOLEX INC. & SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION
		s8500103 s81	
TITLE		SHEET NO.	DATE
64 pos. Male connector acc. DIN 41612 style B contacts arrangement		1 OF 1	95/05/24
PART NO.		DWG NO.	SIZE
85001-0385		SDA-85001-0385	A

