

PC2415N 2.4 GHz Directional Yagi Antenna

MARKETS

• WiMAX

Innovative **Technology** for a **Connected** World

2.4 GHz DATA TRANSMISSION YAGI

The PC2415N provides users with a rugged, easy to install, high-gain directional antenna for deploying 2.4 GHz point-to-point bridges, and can also be used as an access point antenna in long, narrow coverage environments like a tunnel. The antenna offers 13.9 dBi of gain and a very symmetrical and uniform pattern characteristic. The antenna comes equipped with 12" of coax and N female connector. The PC2415N can be installed in either horizontal or vertical polarization and the design incorporates weep holes that are positioned to function regardless of polarization (a sealing system is provided for unused holes).

FEATURES

- UV stable housing
- One-piece brass radiating element
- Advanced microwave substrate
- Stainless steel hardware
- UltraLink[®] pigtail

MODEL	PC2415N
Frequency (MHz)	2400-2500
Gain	13.9 dBi
Number Elements	15
Front-to-Back Ratio	18 dB
E-Plane (3 dB beamwidth)	30°
H-Plane (3 dB beamwidth)	34°
Radiating Element	Brass
Impededance (Ohms)	50
RF Connector (f)	Ν
Weight lb. (kg)	1.25 (.56)
Mounting	Mast mounted with U-Bolts & Brackets
Dimensions in.(cm)	26.5 x 3.75 x 1.5 (67.3 x 9.5 x 3.8)
Enclosure	UV Stable Polycarbonate
Mast Diameter Max. in (cm)	2.125 (5.4)
Ultralink Cable in (cm)	12 (30.5)



PC2415N

global solutions: local support...

Americas: +1.847 839.6907 IAS-AmericasEastSales@lairdtech.com

Europe: +1.32.80.7866.12 IAS-EUSales@lairdtech.com

Asia: +1.65.6.243.8022 IAS-AsiaSales@lairdtech.com

www.lairdtech.com

ANT-DS-PC2415N 0611

Any information furnished by Laird Technologies, Inc. and its agents is believed to be accurate and reliable. All specifications are subject to change without notice. Responsibility for the use and application of Laird Technologies materials rests with the end user, since Laird Technologies and its agents cannot be aware of all potential uses. Laird Technologies materials are sto by moranities as to the fitness, merchantability or suitability of any Laird Technologies materials or products for any specific or general uses. Laird Technologies shall not be liable for incidental or consequential damages of any kind. All Laird Technologies is products are sold pursuant to the Laird Technologies (any kind. All Laird Technologies) or any kind. All Laird Technologies (and any kind. All Laird Technologies) or any kind. All Laird Technologies (and any kind. All Laird Technologies) or any kind. All Laird Technologies (and any kind. All Laird Technologies) or any kind. All Laird Technologies (and any kind. All Laird Technologies) or any kind. All Laird Technologies (and any kind. All Laird Technologies) or any kind. All Laird Technologies (and any kind. All Laird Technologies) or any kind. All Laird Laird (Laird (Laird Technologies) (and any kind. All Laird Technologies) or any kind (and ther marks are trade marks or registered trade marks or laird Technologies, inc. and any taind technologies (and therein) provides a license under any Laird Technologies (and any and therein) provides all lerense under any Laird Technologies (and any and therein) provides all lerense under any taind Technologies (and any taind technologies) (and any taind technologies) (and any taind technologies) (and any taind technologies) (and therein) provides all lerense under any taind Technologies any thind party infeltecual property rights.