



Identification	Part No.	Drawing	Dimensions in mm
----------------	----------	---------	------------------

Hybrid fibre optic cable, multi mode, double ended
 2 x G50/125 + 3 x 2.5 mm²

Length: a = 1 m AC version
 DC version

 a = 5 m AC version
 DC version

 a = 10 m AC version
 DC version

 a = 20 m AC version
 DC version

 a = 40 m AC version
 DC version

 a = 50 m AC version
 DC version

 a = 100 m AC version
 DC version

33 57 211 0015 001
 33 57 211 0015 002

33 57 211 0055 001
 33 57 211 0055 002

33 57 211 0105 001
 33 57 211 0105 002

33 57 211 0205 001
 33 57 211 0205 002

33 57 211 0405 001
 33 57 211 0405 002

33 57 211 0505 001
 33 57 211 0505 002

33 57 211 1005 001
 33 57 211 1005 002

double ended

a = length

Protection level: IP 65 / IP 67

Hybrid fibre optic cable, multi mode, single ended
 2 x G50/125 + 3 x 2.5 mm²

Length: a = 1 m AC version
 DC version

 a = 5 m AC version
 DC version

 a = 10 m AC version
 DC version

 a = 20 m AC version
 DC version

 a = 40 m AC version
 DC version

 a = 50 m AC version
 DC version

 a = 100 m AC version
 DC version

33 57 111 0015 001
 33 57 111 0015 002

33 57 111 0055 001
 33 57 111 0055 002

33 57 111 0105 001
 33 57 111 0105 002

33 57 111 0205 001
 33 57 111 0205 002

33 57 111 0405 001
 33 57 111 0405 002

33 57 111 0505 001
 33 57 111 0505 002

33 57 111 1005 001
 33 57 111 1005 002

single ended

a = length

Hybrid fibre optic cable, multi mode, 50 µm

Length: 10 m 33 57 851 0100 002

Length: 20 m 33 57 851 0200 002

Length: 500 m 33 57 851 5000 002

33 57 851 0100 002

33 57 851 0200 002

33 57 851 5000 002

PVC jacket

2 x G50/125 + 3 x 2.5 mm²

Outer diameter: 12.6 mm

Min. bending radius:

single: 5 x OD

repeated: 10 x OD