

Features

- Low RDS(on)
- Operated at Low Logic Level Gate Drive
- Epoxy Meets UL 94 V-0 Flammability Rating
- Moisture Sensitivity Level 1
- Halogen Free. "Green" Device ^(Note 1)
- Lead Free Finish/RoHS Compliant ("P" Suffix Designates RoHS Compliant. See Ordering Information)

Maximum Ratings

- Operating Junction Temperature Range : -55°C to +150°C
- Storage Temperature Range: -55°C to +150°C
- Thermal Resistance: 833°C/W Junction to Ambient^(Note 2)



Parameter	Symbol	Rating	Unit
Total Power Dissipation	P _D	150	mW
N-Channel MOSFET			
Drain-Source Voltage	V _{DS}	20	V
Gate-Source Voltage	V _{GS}	±12	V
Continuous Drain Current	I _D	0.75	A
Pulsed Drain Current ^(Note 3)	I _{DM}	3	A
P-Channel MOSFET			
Drain-Source Voltage	V _{DS}	-20	V
Gate-Source Voltage	V _{GS}	±12	V
Continuous Drain Current	I _D	-0.6	A
Pulsed Drain Current ^(Note 3)	I _{DM}	-3	A

Note: 1. Halogen free "Green" products are defined as those which contain <900ppm bromine, <900ppm chlorine (<1500ppm total Br + Cl) and <1000ppm antimony compounds.

2. Surface Mounted on FR-4 Board Using Minimum Pad Size.


3. Pulse Width Limited by Maximum Junction Temperature.

Internal Structure and Marking Code



Dual N&P-Channel MOSFET

SOT-563



DIM	INCHES		MM		NOTE
	MIN	MAX	MIN	MAX	
A	0.006	0.011	0.15	0.30	
B	0.043	0.051	1.10	1.30	
C	0.059	0.067	1.50	1.70	
D	0.020		0.50		TYP.
G	0.035	0.043	0.90	1.10	
H	0.059	0.067	1.50	1.70	
K	0.022	0.026	0.55	0.65	
L	0.004	0.011	0.10	0.30	
M	0.004	0.007	0.10	0.18	

N-Channel MOSFET Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=250\mu A$	20			V
Gate-Source Leakage Current	I_{GSS}	$V_{DS}=0V, V_{GS}=\pm 10V$			± 10	μA
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=20V, V_{GS}=0V$			1	μA
Gate-Threshold Voltage ^(Note4)	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=250\mu A$	0.5	0.74	1.1	V
Drain-Source On-Resistance ^(Note4)	$R_{DS(on)}$	$V_{GS}=4.5V, I_D=500mA$		210	300	$m\Omega$
		$V_{GS}=2.5V, I_D=400mA$		300	400	$m\Omega$
		$V_{GS}=1.8V, I_D=200mA$		520	700	$m\Omega$
Forward transconductance	g_{FS}	$V_{DS}=10V, I_D=500mA$	0.8			S
Diode Forward Voltage ^(Note4)	V_{SD}	$V_{GS}=0V, I_S=500mA$			1.2	V
Dynamic Characteristics^(Note5,6)						
Input Capacitance	C_{iss}	$V_{DS}=16V, V_{GS}=0V, f=1MHz$		33		pF
Output Capacitance	C_{oss}			20		
Reverse Transfer Capacitance	C_{rss}			10		
Total Gate Charge	Q_g	$V_{GS}=4.5V, V_{DS}=10V, I_D=1A$		800		pC
Gate-Source Charge	Q_{gs}			290		
Gate-Drain Charge	Q_{gd}			160		
Turn-On Delay Time	$t_{d(on)}$	$V_{GS}=4.5V, V_{DS}=10V, I_{DS}=0.5A, R_G=10\Omega$		4		ns
Turn-On Rise Time	t_r			18		
Turn-Off Delay Time	$t_{d(off)}$			11.6		
Turn-Off Fall Time	t_f			24		

P-Channel MOSFET Electrical Characteristics @ 25°C (Unless Otherwise Specified)

Parameter	Symbol	Test conditions	Min	Typ	Max	Unit
Static Characteristics						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	$V_{GS}=0V, I_D=-250\mu A$	-20			V
Gate-Threshold Voltage ^(Note 4)	$V_{GS(th)}$	$V_{DS}=V_{GS}, I_D=-250\mu A$	-0.5	-0.64	-1.1	V
Zero Gate Voltage Drain Current	I_{DSS}	$V_{DS}=-20V, V_{GS}=0V$			-1.0	μA
Gate-body Leakage Current	I_{GSS}	$V_{GS}=\pm 10V, V_{DS}=0V$			± 10	μA
Drain-Source On-Resistance ^(Note 4)	$R_{DS(on)}$	$V_{GS}=-4.5V, I_D=-500mA$		0.62	0.85	Ω
		$V_{GS}=-2.5V, I_D=-300mA$		0.9	1.2	
		$V_{GS}=-1.8V, I_D=-200mA$		1.4	2.0	
Forward transconductance	g_{FS}	$V_{DS}=-10V, I_D=-500mA$	0.8			S
Diode Forward Voltage ^(Note 4)	V_{SD}	$V_{GS}=0V, I_S=-500mA$			-1.2	V
Dynamic Characteristics^(Note 5,6)						
Input Capacitance	C_{iss}	$V_{DS}=-16V, V_{GS}=0V, f=1MHz$		40		pF
Output Capacitance	C_{oss}			16		
Reverse Transfer Capacitance	C_{rss}			11		
Total Gate Charge	Q_g	$V_{GS}=-4.5V, V_{DS}=-10V, I_D=-1A$		860		pC
Gate-Source Charge	Q_{gs}			320		
Gate-Drain Charge	Q_{gd}			200		
Turn-on Delay Time	$t_{d(on)}$	$V_{DS}=-10V, V_{GS}=-4.5V, I_D=-500mA, R_G=10\Omega$		3.8		ns
Turn-off Delay Time	$t_{d(off)}$			9.4		
Rise Time	t_r			19		
Fall Time	t_f			23		

Note 4. Pulse Test : Pulse Width $\leq 300\mu s$, Duty Cycle $\leq 2\%$.

5. Switching characteristics are independent of operating junction temperature.

6. Guaranteed by Design, Not Subject to Production Testing.

Curve Characteristics(N-Channel)

Fig. 1 - Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - $R_{DS(ON)}$ — I_D




Fig. 4 - $R_{DS(ON)}$ — V_{GS}




Fig. 5 - I_S — V_{SD}





Fig. 6 - Threshold Voltage



Curve Characteristics(N-Channel)

Fig. 7 - Capacitance Characteristics





Fig. 8 - Gate Charge



Curve Characteristics(P-Channel)

Fig. 1 - Typical Output Characteristics




Fig. 2 - Transfer Characteristics




Fig. 3 - $R_{DS(ON)}$ — I_D




Fig. 4 - $R_{DS(ON)}$ — V_{GS}




Fig. 5 - I_S — V_{SD}







Fig. 6 - Threshold Voltage



Curve Characteristics(P-Channel)



Ordering Information

Device	Packing
Part Number-TP	Tape&Reel: 3Kpcs/Reel

IMPORTANT NOTICE

Micro Commercial Components Corp. reserves the right to make changes without further notice to any product herein to make corrections, modifications , enhancements , improvements , or other changes . **Micro Commercial Components Corp.** does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights ,nor the rights of others . The user of products in such applications shall assume all risks of such use and will agree to hold **Micro Commercial Components Corp.** and all the companies whose products are represented on our website, harmless against all damages. **Micro Commercial Components Corp.** products are sold subject to the general terms and conditions of commercial sale, as published at <https://www.mccsemi.com/Home/TermsAndConditions>.

LIFE SUPPORT

MCC's products are not authorized for use as critical components in life support devices or systems without the express written approval of Micro Commercial Components Corporation.

CUSTOMER AWARENESS

Counterfeiting of semiconductor parts is a growing problem in the industry. Micro Commercial Components (MCC) is taking strong measures to protect ourselves and our customers from the proliferation of counterfeit parts. MCC strongly encourages customers to purchase MCC parts either directly from MCC or from Authorized MCC Distributors who are listed by country on our web page cited below. Products customers buy either from MCC directly or from Authorized MCC Distributors are genuine parts, have full traceability, meet MCC's quality standards for handling and storage. **MCC will not provide any warranty coverage or other assistance for parts bought from Unauthorized Sources.** MCC is committed to combat this global problem and encourage our customers to do their part in stopping this practice by buying direct or from authorized distributors.