

 ${\sf B}$

NOTES:

- 1. UL LISTED AND CSA CERTIFIED FOR:
 - A. #22-18 AWG STRANDED COPPER WIRE ONLY
 - B. 221°F [105°C] MAX. OPERATING TEMPERATURE
 - C. 600V MAX VOLTAGE RATING
- 2. MATERIAL:
 - A. STAMPING: .010" [0,25mm] THK BRASS, TIN PLATED
 - B. HOUSING: PREMIUM GRADE NYLON FOR SUPERIOR STRAIN RELIEF INSULATION CRIMPING. COLOR - RED OPAQUE
- 3. SEE www.panduit.com FOR PACKAGE QUANTITIES
- 4. INSERTION/WITHDRAWAL FORCES:
 - A. 1ST INSERTION MAX: 12 lbs. [53 N]
 - B. 1ST WITHDRAWAL MAX: 14 lbs. [62 N]
 - C. 1ST WITHDRAWAL MIN: 2 lbs. [9 N]
- 5. DIMENSIONS IN BRACKETS ARE METRIC EQUIVALENT
- 6. WIRE STRIP LENGTH: $7/32^{\circ} + \frac{1}{32}$ [5,6mm $^{+0.8}_{-0}$]

PANDUIT		WIRE RANGE	MAX WIRE	MIN WIRE	DIMENSIONS - in		02 0 ± [0,51] .16 [4,06]
PART #	TAB SIZE	AWG / mm²	INSUL. DIA.	INSUL. DIA.	$A \pm \frac{.02}{[0,51]}$	B ± .01 [0,25]	l C ±
DPF18-110FIB	.110 X .032 [2,8 X 0,8]	22-18 [0,5-1,0]	.132 [3,35]	.080 [2,03]	.71 [18,0]	.19 [4,38]	
DPF18-111FIB	.110 X .020 [2,8 X 0,5]	22-18 [0,5-1,0]	.132 [3,35]	.080 [2,03]	.71 [18,0]	.19 [4,38]	.16 [4,06]

UL & CSA TOOLS (DIES) CT-520 CT-1525 (A POCKET)

CT-2500 (CT-2525CH: A PKT)

TITLE





В

Α

						DISCOGRIP, LOOSE PIECE FULLY INSULATED FEMALE DISCONNECTS .110 X .032, .110 X .020 TAB					
Α											
	08	5/17	JHNU	TMR	RGB	ADDED CT-2500 TOOL, PACKAGE QUANTITIES NOTE, I/W FORCES	A41464	ITEM REVISION NAME	WING		
	07	2/07	DAW	DAW	LCA	ADDED POCKET A NOTE TO CT-1525	TR00220	N41464BA/08 DATASET FILE NAME N41464BA/08		PANDUIT	
	06	7/03	KLFU	SKB	LCA	UPDATE GEOMETRY, WIRE RANGE WAS 0,5-1,5	12453				
	05	1/01	RM	SKB	JAC	FILESPEC WAS N41464AA_PCD_04	8933				
	04		JKD			ADDED CT-1525 TOOL	07632	.x ± .1 [2.54] .xxx .xx ± .01 [.25] ANGLES	± .005 [.127] ± 5 °	SEE NOTES	
JA/20	03	10/96	ТМ	RLS	LA	UPDATED NOTES AND DIMENSIONS	05139		HIRD ANGLE ROJECTION	DRAWING NUMBER:	
10100	REV	DATE	ВҮ	СНК	APR	DESCRIPTION	ECN	DRAWN BY DATE CHK	SCALE	SHT 1 0F 1	SIZE