

ioLogik E4200

Modular Ethernet remote I/O adaptor



- > Active communication with patented Active OPC Server
- > Two independent Ethernet LANs
- > Allow up to 16-module expansion without needing a backplane
- > Front-end intelligence with patented Click&Go control logic up to 80 rules
- > Smart alarm management with e-mail, SNMP Trap, TCP, UDP
- > Friendly configuration via web browser
- > Simplify I/O management with MXIO library on Windows or Linux platform
- > Support SNMPv1/v2c protocol

Introduction

The ioLogik E4200 is suitable for remote monitoring and alarm systems, such as those used for water treatment systems, water supply systems, wastewater treatment systems, and power monitoring systems. These kinds of applications need more I/O points and a

variety of I/O types, including temperature sensors, gas detectors, and water quality detectors, all of which can benefit from the versatile mixture of I/O features supported by the ioLogik E4200.

Specifications

LAN

Ethernet: 2 x 10/100 Mbps: 2 MACs, 2 IPs, RJ45 connectors

Protection: 1.5 KV magnetic isolation

Protocols: Modbus/TCP, TCP/IP, UDP, DHCP, Bootp, SNMP, HTTP, SNTp, SMTP

Serial Communication

Interface: 1 x RS-232 (9-pin D-Sub, male)

Parameters: N, 8, 1

Baudrate: 115,200 bps

Power Requirements

Power Input: 24 VDC nominal, 12 to 36 VDC

Power Consumption: 175 mA @ 24 VDC

Current for I/O Modules: Max. 1.5A @ 5 VDC

Field Power

Rated Voltage: 11 to 28.8 VDC, 24 VDC typical

Current in Field Power Contact: Max. 10 A

Isolation

System Power to I/O Driver: Optical isolation

Physical Characteristics

Dimensions: 45 x 99 x 70 mm (1.77 x 3.90 x 2.76 in)

Note: Please see pages 15-23 for the dimensions diagram.

Weight: 180 g

Mounting: DIN rail

Environmental Limits

Operating Temperature: -10 to 60°C (14 to 140°F)

Storage Temperature: -40 to 85°C (-40 to 185°F)

Ambient Relative Humidity: 5 to 95% (non-condensing)

Altitude: Up to 2000 m

Note: Please contact Moxa if you require products guaranteed to function properly at higher altitudes.

Standards and Certifications

Safety: UL 508

EMI:

61000-3-2; EN 61000-3-3; EN 61000-6-4; FCC Part 15, Subpart B, Class A

EMS:

EN 61000-4-2, EN 61000-4-3, EN 61000-4-4, EN 61000-4-5, EN 61000-4-6, EN 61000-4-8, EN 61000-6-2, IEC 61000-4-11

Shock: IEC 60068-2-27

Freefall: IEC 60068-2-32

Vibration: IEC 60068-2-6

Green Product: RoHS, CRoHS, WEEE

Note: Please check Moxa's website for the most up-to-date certification status.

MTBF (mean time between failure)

Time: 357,000 hrs

Database: Telcordia (Bellcore)

Warranty

Warranty Period: 2 years

Details: See www.moxa.com/warranty

Ordering Information

Step 1: Select a network adaptor module

ioLogik E4200



Step 2: Select I/O modules

M-1000/2000/3000/4000/6000 Series



Step 3: Select power modules

M-7000 series

Package Checklist

- ioLogik E4200
- I/O modules ordered
- Power modules ordered
- Documentation and software CD
- Quick installation guide (printed)

ioLogik E4200: Modular Ethernet remote I/O adaptor with RJ45 connectors, 2 MACs, up to 16 I/O modules, -10 to 60°C operating temperature

**Note: The ioLogik E4200 Modular Ethernet remote I/O adaptor can be expanded with up to 16 I/O modules.*