

1U Rack-Mount Power Strip, 120V, 15A, 5-15P, 12 Right-Angle 5-15R Outlets (6 Front-Facing, 6 Rear-Facing), 15 ft. (4.57 m) Cord

MODEL NUMBER: RS-1215-RA



Highlights

- 12 NEMA 5-15R outlets are spaced apart to accommodate bulky transformers
- Lighted on/off switch with plastic cover is protected against accidental turn-off
- 15 ft. cord with NEMA 5-15P plug is long enough to reach distant AC outlet
- Versatile installation on wall, under counter or in 1U of rack space

Package Includes

- RS-1215-RA 1U Rack-Mount Power Strip
- Owner's manual

Delivers 120V power to rack-mount equipment in your network closet or server room.

Features

12-Outlet Power Strip for Your Rack Equipment

This 120V power strip is a versatile all-metal cabinet with 12 NEMA 5-15R outlets — six in front and six in back. The outlets are widely spaced to accommodate bulky transformers without blocking any outlets. Unfiltered electrical pass-through makes the RS-1215-RA ideal for distributing alternate waveform UPS or generator power in your data center or network closet's rack enclosure. The outlets are oriented at a right angle with the ground pin at the bottom.

Features Safety Standards and Versatile Installation Options

A lighted power switch with snap-in switch guard confirms on/off status at a glance and helps prevent accidental shutdowns. A 15A circuit breaker protects connected equipment. Detachable mounting brackets allow installation on a wall, under a counter or in 1U of space in an EIA-standard 19-inch rack. The 15-foot (4.6-meter) power cord with NEMA 5-15P plug connects to a compatible AC outlet.

Specifications

| OVERVIEW | |
|------------------------------------|--------------|
| UPC Code | 037332099402 |
| INPUT | |
| Nominal Input Voltage(s) Supported | 120V AC |
| Recommended Electrical Service | 15A 120V |
| Voltage Compatibility (VAC) | 120 |
| Input Plug Type | NEMA 5-15P |

| | |
|--|--|
| Input Cord Length (ft.) | 15 |
| Right-Angle Plug | No |
| Input Cord Length (m) | 4.57 |
| Integrated Cord Clip | No |
| OUTPUT | |
| Frequency Compatibility | 50 / 60 Hz |
| Output Receptacles | (12) 5-15R |
| Circuit Breaker (amps) | 15 |
| Transformer Accommodation | (9) Yes |
| Outlet Orientation | 6 front-facing / 6 rear-facing, all with ground pin oriented to the bottom (when viewed in 1U rackmount configuration) |
| Right-Angle Outlets | Yes |
| USER INTERFACE, ALERTS & CONTROLS | |
| Switches | Lighted 2 position switch controls power to all outlets |
| Locking Switch Cover | Transparent locking switch cover prevents accidental shutoff |
| PHYSICAL | |
| Color | Black |
| Material of Construction | Metal |
| Power Cord Color | Black |
| Form Factors Supported | 1U rackmount, wall-mount and undercounter installation supported |
| Housing Color | Black |
| Included Mounting Accessories | Rackmount flanges |
| Mounting Holes or Slots | No |
| Outlets Measurement (Center to Center) | Distance between Front outlets = 2.03 in.; Distance between Rear outlets = 2.79 in. |
| Receptacle Color | Black |
| Shipping Dimensions (hwd / in.) | 9.30 x 2.25 x 20.30 |
| Shipping Dimensions (hwd / cm) | 23.62 x 5.72 x 51.56 |
| Shipping Weight (lbs.) | 5.32 |
| Shipping Weight (kg) | 2.41 |
| Unit Dimensions (hwd / in.) | 1.750 x 19.000 x 4.000 |
| Unit Dimensions (hwd / cm) | 4.445 x 44.45 x 11.4 |
| Unit Weight (lbs.) | 4.6 |
| Unit Weight (kg) | 2.09 |

| ENVIRONMENTAL | |
|-------------------------------------|---------------------------------------|
| Operating Temperature Range | 32° to 113°F (0° to 45°C) |
| FEATURES & SPECIFICATIONS | |
| Rotatable Outlets | No |
| Antimicrobial | No |
| Built-In Circuit Breaker | Yes |
| Grounding | Back panel nut and bolt grounding lug |
| STANDARDS & COMPLIANCE | |
| Product Certifications | cUL Listed; UL 1363; UL Listed |
| Product Compliance | RoHS |
| WARRANTY & SUPPORT | |
| Product Warranty Period (Worldwide) | Lifetime limited warranty |