



TOLERANCES:	
10 UNDER	±0.2
10 OVER	±0.25
30 UNDER	±0.3
ANGLE	±3°

<誤嵌合防止キー (極性) タイプ> <POLARITY KEY TYPE>

51239-2001	51239-2002	51239-2003	51239-2004	51239-2005
STANDARD TYPE	A TYPE	B TYPE	C TYPE	D TYPE

C-4	D	51239-2005	51239-**0*	20
C-3	C	51239-2004		
B-3	B	51239-2003		
B-2	A	51239-2002		
—	STANDARD	51239-2001		
POLARITY POSITION (CIRCUIT No.)	POLARITY TYPE	MATERIAL No.	MODEL No.	CIRCUIT

注記 NOTES

- 材質 MATERIAL
ガラス入りPBT樹脂 UL94V-0 色:黒
HOUSING : PBT G.F. UL94V-0 COLOR : BLACK
- 適用端子 : 56120-8*90 , 56121-8*90
APPLICABLE CRIMP PIN : 56120-8*90 , 56121-8*90
- 適用シェルボディ : 56380-2000
APPLICABLE SHELL BODY : 56380-2000
- 適用シェルカバー : 56381-2000
APPLICABLE SHELL COVER : 56381-2000
- 嵌合相手 : 51233-201*
MEET WITH : 51233-201*

DRAWING CORRECTION	QUALITY SYMBOLS
EC NO: PG2017-0285	▽=0
DRW:BRUPERT 2016/09/14	▽=0
CHKD: BWOODMAN	
APPR: BWOODMAN 2016/09/16	
REV	DESCRIPTION
B	

GENERAL TOLERANCES (UNLESS SPECIFIED)	
mm	INCH
4 PLACES ± --- ± ---	
3 PLACES ± --- ± ---	
2 PLACES ± --- ± ---	
1 PLACE ± --- ± ---	
0 PLACE ± --- ± ---	
ANGULAR ± 5°	
DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	

DIMENSION STYLE MM ONLY	
DRAWN BY	DATE
BRUPERT	2016/09/14
CHECKED BY	DATE
APPROVED BY	DATE
BWOODMAN	2016/09/16
MATERIAL NO.	
AS NOTED	
SIZE	
B	

SCALE	DESIGN UNITS	THIRD ANGLE PROJECTION
2:1	METRIC	
TITLE		
COMPACT ROBOT CONN.(CRC) PLUG SOCKET HS'G		
molex		
MATERIAL NO.	DOCUMENT NO.	SHEET NO.
	SD-51239-005	1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION		