

DIMENSIONS No. OF В С PINS 1.213 0.984 0.666 9 30.81 24.99 16.92 1.541 1.312 0.994 15 39.14 33.32 25.25 2.088 1.852 1.534 25 53.04 47.04 38.96 2.729 2.500 2.181 37 69.32 63.50 55.42

MATERIALS:

SHELL: SPCC, NICKEL PLATED
INSULATOR: BLACK PA9T NYLON, UL 94V-O
CONTACTS: BRASS, GOLD PLATED


RIVET: COPPER ALLOY, NICKEL PLATED
SCREWLOCK: ZINC ALLOY, NICKEL PLATED

BOARDLOCK: SPCC, TIN PLATED

ELECTRICAL:


CURRENT RATING: 5 AMPS

INSULATOR RESISTANCE: 1,000 MEGOHMS Min.
DIELECTRIC WITHSTANDING: 1,000VAC RMS
TEMPERATURE: -55° C to +105° C




BOTTOM VIEW

ROHS COMPLIANT




DO NOT SCALE FROM DRAWING



	0.141 ±0.020	METAL SHELL	METAL SHELL FORK BOARD LOCKS	0.500 METAL SHELL FORK BOARD LOCKS
0.120" DIA. HOLE	16	N/A	N/A	55
4-40 FLUSH INSERT	17	45	57 BOARD LOCKS IN REAR HOLE (0.590")	53 BOARD LOCKS IN FRONT HOLE (0.590")
4-40 HEX STANDOFF FEMALE SCREWLOCK	18	48	54 BOARD LOCKS IN REAR HOLE	56 BOARD LOCKS IN FRONT HOLE
4-40 ROUND STANDOFF FEMALE SCREWLOCK	N/A	N/A	N/A	N/A

DO NOT SCALE FROM DRAWING



ROHS COMPLIANT