






P.C.B. HOLE DRILLINGS  
 (P.C.B. TOP SIDE)



NOTES:

1. RoHS COMPLIANT
2. FOR WAVESOLDERING (SOLDER BATH TEMPERATURE 260 °C FOR 5 SEC. AND SOLDER PREHEAT 100 °C FOR 30 SEC.)
3. METALSHELLS: STEEL; min. 315µm TIN over 40-80µm NICKEL
4. INSULATOR: HIGH TEMPERATURE PLASTIC UL 94 V-0; BLACK
5. CONTACTS: COPPER ALLOY  
PLATING: GOLD FLASH over NICKEL
6. THREADED SPACER CLIPS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL  
PCB-HOLE: Ø3,1 ± 0,1; PCB-THICKNESS 2,3mm
7. COLLARS: COPPER ALLOY; min. 200µm TIN over 80µm NICKEL
8. SEALING COMPOUND: PUR; BLUE
9. CAPACITANCE: 830pF ± 20%
10. DIELECTRIC WITHSTANDING VOLTAGE: 707 VDC
11. CONNECTOR IS PART MARKED: HFC3XSRAA19H831X CONEC ABC

(b)

Directive 2002/95/EC RoHS compliant

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH DO NOT ALTER CAD DRAWING BY HAND	tolerance		dim. in mm		scale: 2:1 (5:1)
	date		name		material: see notes
	drawn	22.11.10	Henneboel		title: D-SUB HD C-FILTER FEMALE 44pos. SOLDER PIN STRAIGHT with threaded spacer clip
	appd.	22.11.10	Koch		
	norm				
d-old				dwg no: Inventor 10	
1 x b	A3958	31.03.2011	K.H.		DIN-A3
a	Origin				24K1A1283
rev.	description	date	name	part no: HFC3XSRAA19H831X	