






LOC	DIST	P	F	ZONE	LTR	DESCRIPTION	DATE	APPD
AF	50					C REVISED PER 061A-0199-98	11/JUN/98	PF/DD



- PART ACCEPTS .125 RECEPTACLE CONTACT PART NO 770642-1.
- PART MATES WITH .125 BLADE PLUG HOUSING PART NO 521075-1 AND 96-1192-3-1.
- THIS MATERIAL HAS A 125°C ELECTRICAL TEMPERATURE INDEX RATING BY UL AND A UL 94 V-2 FLAMMABILITY RATING.

521076-1
PART NO

DO NOT SCALE PRINT. UNLESS SPECIFIED DIMENSIONS IN mm [INCHES] TOLERANCES ON : 2 PLC DEC ± 0.25 [.010] 3 PLC DEC ± - ANGLES ± -	DR 17/SEP/97 PHILLIP M FORTNEY	AMP Incorporated Harrisburg, PA 17105-3608		
	CHK 17/SEP/97 JEFF RUTH			NAME
MATERIAL NYLON 6/6	APPD 17/SEP/97 DON DECKER	PLUG, 9 CIRCUIT, 3.18 [.125] BLADE		
FINISH COLOR-BLACK	APPD 17/SEP/97 SUE WRIGHT			
	PRODUCT SPEC -	SIZE C	CAGE CODE 00779	DRAWING NO C=521076
	APPLICATION SPEC -	SCALE 4:1	SHEET 1 OF 1	
	WEIGHT -			

THIS DRAWING IS A CONTROLLED DOCUMENT FOR AMP INCORPORATED. IT IS SUBJECT TO CHANGE AND THE CONTROLLING ENGINEERING ORGANIZATION SHOULD BE CONTACTED FOR THE LATEST REVISION.