## 48 INCHES LENGTH





Connector A 132114RP SMA Plug Straight Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 034-5019 HD-BNC Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

## **Assembly & Label Notes**

Assembly label to be placed  $\sim$  2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector A			Cable		Connector B	
Part #:	132114RP	Part #:	RG-174	Part #:	034-5019	
Description:	SMA PLUG RP RG316 500	Description:	RG-174 - PE 0.1	Description:	HD-BNC BHD JK RG316 500	
Type:	SMA	Dielectric:	PE	Type:	HD-BNC	
Gender:	Plug	Shielding:	Braid	Gender:	Jack	
Body Type:	Straight	Diameter:	0.1	Body Type:	Straight	
Contact Type:	Crimp	Impedance:	50 Ohm	Contact Type:	Solder	
Polarity:	Reverse	Sheathing:	None	Polarity:	Standard	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Mounting:	Cable	Length:	48 Inches	Mounting:	Bulkhead - Rear Mount	
Body Material:	Brass			Body Material:	Brass	
Body Finish:	Gold			Body Finish:	Nickel	
IP Rating:	None			IP Rating:	None	
Contact Material:	Beryllium Copper			Contact Material:	Beryllium Copper	
Contact Finish:	Gold			Contact Finish:	Gold	
Max. Freq.:	12.4 GHz			Max. Freq.:	6 GHz	
Booting:	SMA Plug Straight RP			Booting:	HD-BNC Jack Straight BHD	
				Clocking:	0°	



THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-ST-PL-RP/HDBNC-ST-JK G174 48I

Part No

Q-6800P0003048I

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES