



Recommended Cable Stripping Dim's

NOTES: Finish (Plating Thickness in Micro-inches)  
 1. Brass  
 2. Nickel Pl. 100 Min. Thick over Copper Pl. 50 Min. Thick  
 3. Phosphor Bronze  
 4. Gold Pl. 3 Min Thick over Nickel Pl. 50 Min. Thick over Copper Pl. 50 Min. Thick  
 5. TEFLON

Crimped Ferrule  
 Hex Crimp Size .213 (5.4)  
 Crimped Contact Pin  
 Hex Crimp Size .068 (1.7)

RoHS Compliant

10	Ferrule	Copper	Note 2	1	
9	Contact Pin	Note 2	Note 4	1	
8	Shell	Note 1	Note 2	1	
7	Gasket	Rubber	red	1	
6	Retainer Ring	Note 1	Note 2	1	
5	Spring	SK5	Note 2	1	
4	Washer	Note 1	Note 2	1	
3	Barrel	Note 1	Note 2	1	
2	Insulator	Note 5	Natural	1	
1	Body	Note 1	Note 2	1	
No	Description	Material	Finish	Q'ty	Drawing No.

Dimensions are in Inches  
 Unless Otherwise Specified  
 Tolerances  
 0.5-6 = ±0.2  
 6-30 = ±0.4  
 30-120 = ±0.6  
 120-315 = ±1  
 315-1000 = ±1.6  
 1000-2000 = ±2.4

Part No.	
Approved	Date 12-14-2018
Checked	Date 12-14-2018
Drawn	Date 12-14-2018

<b>NTE Electronics</b>	
Title	BNC Reverse Polarity Crimp Plug (For RG-58C/U Cable)
Drawing No.	06-B028
File No.	

No	Description	Material	Finish	Q'ty	Drawing No.	Scale	3/1	Issue	A
----	-------------	----------	--------	------	-------------	-------	-----	-------	---