

## Interface module - VIP-3/PT/HD26SUB/M - 2904269

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)



VARIOFACE module, with push-in connection and high density D-subminiature male connector, for mounting on NS 35 rails, no. of pos.: 26

The figure shows the 44-pos. version with D-SUB plug.



### Key commercial data

Packing unit	1 pc
Weight per Piece (excluding packing)	152.0 GRM
Custom tariff number	85369010
Country of origin	United States

### Technical data

#### Dimensions

Width	52 mm
Height	75.8 mm
Depth	63 mm

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 50 °C
Ambient temperature (storage/transport)	-20 °C ... 70 °C

#### General

Nominal voltage $U_N$	125 V AC/DC
Max. current carrying capacity per branch	1 A
Number of positions	26
Status display	No
Mounting position	any

## Interface module - VIP-3/PT/HD26SUB/M - 2904269

### Technical data

#### General

Standards/regulations	EN 50178
Pollution degree	2
Surge voltage category	II
Rated surge voltage	1.2 kV

#### Connection data for connection 1

Connection name	PCB connection
Connection in acc. with standard	IEC / EN
Connection method	Push-in connection
Number of positions	26
Conductor cross section solid min.	0.14 mm <sup>2</sup>
Conductor cross section solid max.	2.5 mm <sup>2</sup>
Conductor cross section stranded min.	0.14 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Stripping length	8 mm
Screw thread	M3

#### Connection data for connection 2

Connection name	D-SUB connection
Number of connections	1
Connection method	High density D-SUB pin strip
Number of positions	26

### Classifications

#### eCl@ss

eCl@ss 4.0	27250313
eCl@ss 4.1	27250313
eCl@ss 5.0	27250313
eCl@ss 5.1	27250313
eCl@ss 6.0	27242608
eCl@ss 7.0	27141152
eCl@ss 8.0	27141152

#### ETIM

ETIM 3.0	EC001604
----------	----------

# Interface module - VIP-3/PT/HD26SUB/M - 2904269

## Classifications

### ETIM

ETIM 4.0	EC001604
ETIM 5.0	EC001604

### UNSPSC

UNSPSC 6.01	30211824
UNSPSC 7.0901	39121421
UNSPSC 11	39121421
UNSPSC 12.01	39121421
UNSPSC 13.2	39121421

## Approvals

### Approvals


Approvals


CSA / UL Recognized / cUL Recognized / cULus Recognized

Ex Approvals

Approvals submitted

### Approval details

CSA 	
mm <sup>2</sup> /AWG/kcmil	26-14
Nominal current I <sub>N</sub>	1 A
Nominal voltage U <sub>N</sub>	105 V

UL Recognized 	
mm <sup>2</sup> /AWG/kcmil	26-14

# Interface module - VIP-3/PT/HD26SUB/M - 2904269

## Approvals


Nominal current $I_N$	1 A
Nominal voltage $U_N$	125 V

cUL Recognized	
mm <sup>2</sup> /AWG/kcmil	26-14
Nominal current $I_N$	1 A
Nominal voltage $U_N$	125 V

cULus Recognized	
------------------	--

## Drawings

Circuit diagram



Universal circuit diagram

Schematic diagram

