

STRADELLA-8-HB-S

~25° spot beam for industrial applications

SPECIFICATION:

Dimensions	49.5 x 49.5 mm
Height	7.5 mm
Fastening	screw
ROHS compliant	yes ⓘ


MATERIALS:

Component	Type	Material	Colour	Finish
STRADELLA-8-HB-S	Multi-lens	PMMA	clear	

ORDERING INFORMATION:













Component	Qty in box	MOQ	MPQ	Box weight (kg)
C15183_STRADELLA-8-HB-S » Box size:		160	160	5.0













See also our general installation guide: www.ledil.com/installation_guide









OPTICAL RESULTS (MEASURED):

 <p> LED QUICK FLUX XT 2x8 xxx STRDLL G5 FWHM / FWTM 31.0° / 81.0° Efficiency 93 % Peak intensity 1.5 cd/m LEDs/each optic 1 Light colour White Required components: </p>		
 <p> LED J Series 3030 FWHM / FWTM 28.0° / 76.0° Efficiency 96 % Peak intensity 1.8 cd/m LEDs/each optic 1 Light colour White Required components: </p>		
 <p> LED XP-G3 FWHM / FWTM 34.0° / 93.0° Efficiency 94 % Peak intensity 1.3 cd/m LEDs/each optic 1 Light colour White Required components: </p>		
 <p> LED XT-E FWHM / FWTM 28.0° / 83.0° Efficiency 94 % Peak intensity 1.6 cd/m LEDs/each optic 1 Light colour White Required components: </p>		

OPTICAL RESULTS (MEASURED):

<p>LUMILEDS</p> <p>LED LUXEON 3030 2D (Round LES)</p> <p>FWHM / FWTM 23.0° / 66.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 2.3 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>LUMILEDS</p> <p>LED LUXEON 3030 2D (Round LES)</p> <p>FWHM / FWTM 23.0° / 64.0°</p> <p>Efficiency 88 %</p> <p>Peak intensity 2.3 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p> <p>Protective plate, glass</p>		
<p>LUMILEDS</p> <p>LED LUXEON 3535L</p> <p>FWHM / FWTM 24.0° / 66.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 2.3 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		
<p>LUMILEDS</p> <p>LED LUXEON TX</p> <p>FWHM / FWTM 29.0° / 75.0°</p> <p>Efficiency 94 %</p> <p>Peak intensity 1.9 cd/m</p> <p>LEDs/each optic 1</p> <p>Light colour White</p> <p>Required components:</p>		





OPTICAL RESULTS (MEASURED):

<p>LUMILEDS</p> <p>LED LUXEON V2 FWHM / FWTM 31.0° / 81.0° Efficiency 94 % Peak intensity 1.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>NICHIA</p> <p>LED NVSW219D FWHM / FWTM 33.0° / 80.0° Efficiency 94 % Peak intensity 1.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED Duris S5 (2 chip) FWHM / FWTM 23.0° / 64.0° Efficiency 93 % Peak intensity 2.3 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		
<p>OSRAM <small>Opto Semiconductors</small></p> <p>LED OSLON Square CSSRM2/CSSRM3 FWHM / FWTM 27.0° / 78.0° Efficiency 94 % Peak intensity 1.8 cd/lm LEDs/each optic 1 Light colour White Required components:</p>		





OPTICAL RESULTS (MEASURED):







OPTICAL RESULTS (SIMULATED):

<p>CREE → LED</p> <p>LED: XHP35.2 HI FWHM / FWTM: 40.0° / 94.0° Efficiency: 93 % Peak intensity: 1.2 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>CREE → LED</p> <p>LED: XP-P FWHM / FWTM: 20.0° / 62.0° Efficiency: 95 % Peak intensity: 2.8 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>LUMILEDS</p> <p>LED: LUXEON 3535L HE FWHM / FWTM: 20.0° / 65.0° Efficiency: 90 % Peak intensity: 2.3 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	
<p>LUMILEDS</p> <p>LED: LUXEON HR30 FWHM / FWTM: 26.0° / 72.0° Efficiency: 91 % Peak intensity: 2.1 cd/lm LEDs/each optic: 1 Light colour: White Required components:</p>	

OPTICAL RESULTS (SIMULATED):

<p>NICHIA</p> <p>LED NCSxE17A FWHM / FWTM 19.0° / 59.0° Efficiency 94 % Peak intensity 2.9 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>NICHIA</p> <p>LED NF2x757G FWHM / FWTM 29.0° / 76.0° Efficiency 94 % Peak intensity 2 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>NICHIA</p> <p>LED NVSxE21A FWHM / FWTM 22.0° / 67.0° Efficiency 94 % Peak intensity 2.4 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	
<p>NICHIA</p> <p>LED NVSxx19B/NVSxx19C FWHM / FWTM 30.0° / 86.0° Efficiency 88 % Peak intensity 1.6 cd/lm LEDs/each optic 1 Light colour White Required components:</p>	


OPTICAL RESULTS (SIMULATED):

<p>OSRAM Opto Semiconductors</p> <p>LED: OSCONIQ C 2424</p> <p>FWHM / FWTM: 24.0° / 68.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 2.3 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: OSCONIQ P 3030</p> <p>FWHM / FWTM: 21.0° / 58.0°</p> <p>Efficiency: 95 %</p> <p>Peak intensity: 3 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>OSRAM Opto Semiconductors</p> <p>LED: OSCONIQ P 3737 (2W version)</p> <p>FWHM / FWTM: 28.0° / 76.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 2 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p>SAMSUNG</p> <p>LED: LH181B</p> <p>FWHM / FWTM: 27.0° / 75.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 2 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	

OPTICAL RESULTS (SIMULATED):

SAMSUNG


LED LH351B
 FWHM / FWTM 33.0° / 83.0°
 Efficiency 94 %
 Peak intensity 1.7 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



SAMSUNG


LED LH351B
 FWHM / FWTM 33.0° / 82.0°
 Efficiency 88 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:

Protective plate, glass




SAMSUNG

LED LH351C
 FWHM / FWTM 35.0° / 86.0°
 Efficiency 93 %
 Peak intensity 1.6 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:











SAMSUNG

LED LH351D
 FWHM / FWTM 44.0° / 93.0°
 Efficiency 93 %
 Peak intensity 1.2 cd/lm
 LEDs/each optic 1
 Light colour White
 Required components:



OPTICAL RESULTS (SIMULATED):

<p> SEOUL SEMICONDUCTOR</p> <p>LED: Z5M4</p> <p>FWHM / FWTM: 31.0° / 80.0°</p> <p>Efficiency: 94 %</p> <p>Peak intensity: 1.8 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p> SEOUL SEMICONDUCTOR</p> <p>LED: Z5M5</p> <p>FWHM / FWTM: 34.0° / 92.0°</p> <p>Efficiency: 84 %</p> <p>Peak intensity: 1.3 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p> <p style="background-color: #ADD8E6; padding: 2px; display: inline-block;">Protective plate, glass</p>	
<p> SEOUL SEMICONDUCTOR</p> <p>LED: Z5M5</p> <p>FWHM / FWTM: 34.0° / 92.0°</p> <p>Efficiency: 93 %</p> <p>Peak intensity: 1.4 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	
<p> SEOUL SEMICONDUCTOR</p> <p>LED: Z8Y19</p> <p>FWHM / FWTM: 23.0° / 81.0°</p> <p>Efficiency: 92 %</p> <p>Peak intensity: 1.8 cd/lm</p> <p>LEDs/each optic: 1</p> <p>Light colour: White</p> <p>Required components:</p>	

GENERAL INFORMATION:

NOTE: The typical beam angle will be changed by different color, chip size and chip position tolerance. The typical total beam angle is the full angle measured where the luminous intensity is half of the peak value.

MATERIALS:

As part of our continuous research and improvement processes, and to ensure the best possible quality and availability of our products, LEDiL reserves the right to change material grades without notice.

PRODUCT DATA USER AGREEMENT AND DISCLAIMER:

The measured data in the provided downloadable LEDiL Product Datasheets and Mechanical 2D-Drawings is rounded and provided as reference for planning. LEDiL Oy's optical specifications have been verified by conducting performance testing of the products in accordance with the company's quality system. The reported data are averaged results of multiple measurements with typical variation. LEDiL Oy reserves the right to without prior notification make changes and improvements to its products.

LEDiL Oy assumes neither warranty, nor guarantee nor any other liability of any kind for the contents and correctness of the provided data. The provided data has been generated with highest diligence but the provided data may in reality not represent the complete possible variation range of all intrinsic parameters. Therefore, in certain cases a deviation from the provided data could occur.

LEDiL Oy reserves the right to undertake technical changes of its products without further notification which could lead to changes in the provided data. LEDiL Oy assumes no liability of any kind for the possible deviation from any provided data or any other damage resulting from the usage of the provided data.

The user agrees to this disclaimer and user agreement with the download or usage of the provided files.

LEDiL Oy

Joensuunkatu 13
FI-24240 SALO
Finland

LEDiL Inc.

228 West Page Street
Suite D
Sycamore IL 60178
USA

Ledil Optics Technology (Shenzhen) Co., Ltd.

405 , Block B
Casic Motor Building
Shenzhen 518057
P.R.CHINA

Local sales and technical support

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)

Shipping locations

Salo, Finland
Hong Kong, China

Distribution Partners

[www.ledil.com/
where_to_buy](http://www.ledil.com/where_to_buy)