12:1 Dual Laser Infrared Thermometer



Features

- Dual laser targeting
- 12:1 spot ratio
- Wide temperature measurement range
- Auto temperature scan
- 6.6 ft. (2 m) drop protection




12:1 Dual Laser Infrared Thermometer

IR2000A

The Klein Tools IR2000A features a wide temperature measurement range, a tight distance-to-spot ratio, auto temperature scan, a K-type thermocouple input, dual lasers, and several sampling modes to assist you in making the best possible measurements.

Dual Laser Targeting for Specific Measurement Areas:

This dual laser gun accurately measures the temperature of the target area that falls between the two laser points:




12:1 Distance To Spot Ratio for Accurate Temperature Readings:

If you are 12 feet away from an air vent, the vent should be 1 foot or less in diameter in order to attain the most accurate temperature measurement.

Diameter at Spot

Laser dots indicate the measurement diameter:



ľ	•	
°F/°C	-76 to 1022°F / -60 to 550°C	
°F/°C	-83.2 to 2552°F / -64 to 1400°C	
MAX/MIN	•	
*	•	
	•	
0.10 – 1.00		
°F/°C	•	
HI/LO	•	
Apo	60 sec	
4	6.6 ft. (2 m)	
	°F/°C MAX/MIN → °F/°C HI/LO	



Cat. No.	UPC 092644+	Batteries	Height	Width	Depth	Weight (oz.)
IR2000A	69309-0	2 x AAA	6.76" (172 mm)	1.87" (48 mm)	4.7" (119 mm)	9.0 (255g)



A CAUTION: Reflective materials may be hotter than indicated. Laser radiation-Do NOT stare into beam. Class 2 laser product.



See our complete line of Test and Measurement products





