



## Hanging Scales PCE-CS 10000N



PCE-CS 10000N are a digital battery-powered heavy-duty industrial crane, lifter, suspended or hanging scales, dynamometer, electronic balance or weighing hook that displays measurement values in kilograms (kg) or pounds (lbs). The scales are delivered factory calibrated and include a hook, shackle and remote control. For an additional fee, the scales can be calibrated according to ISO standards.

- ▶ Maximum weighing capacity: 10000 kg / 22046 lbs  $\approx$  10 Tons
- ▶ Resolution: 5 kg
- ▶ Tare range: 100% full scale
- ▶ Displays measurement values in kilograms (kg) or pounds (lbs)
- ▶ Comes factory calibrated (see accessories for optional ISO calibration)
- ▶ Includes hook, shackle and remote control
- ▶ Features zero, tare, hold, sum / accumulation, battery voltage indication and adjustable brightness functions

Subject to change

## Specifications

|                        |   |
|------------------------|---|
| Maximum capacity       | 10000 kg / 22046 lbs ≈ 10 Tons                  |
| Minimum weight         | 100 kg / 220.5 lbs                              |
| Resolution             | 5 kg  |
| Standard               | OIML class III                                  |
| Zero range             | 4 % full scale (FS)                             |
| Tare range             | 100 % FS  |
| Settling time          | ≤ 10 seconds                                    |
| Overload indication    | 100 % FS + 9e                                   |
| Max. safety load       | 125 % FS  |
| Ultimate load          | 400 % FS  |
| Display                | 5-digit LCD/LED, 30 mm / 1.18" character height |
| Battery                | 6 V / 7 Ah fully-sealed lead-acid battery       |
| Battery life           | ≥ 50 hours                                      |
| Battery charger        | 9 V DC / 1000 mA                                |
| Remote control range   | 15 m / 49.2'                                    |
| Remote control battery | 2 x 1.5 V AAA batteries                         |
| Operating temperature  | -10 ... +40 °C / +14 ... +104 °F                |
| Operating humidity     | ≤ 85 % RH under +20 °C / +68 °F                 |
| Dimensions             | 264 x 206 x 745 mm / 10.4 x 8.1 x 29.4"         |
| Weight                 | 30 kg / 66.2 lbs                                |

## More information

Manual



More product info



Similar products



Subject to change