# 1-1969572-0 ACTIVE

### **Economy Power 2.5**

TE Internal #: 1-1969572-0

PCB Mount Header, Right Angle, Wire-to-Board, 10 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole -

Solder, Economy Power 2.5

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles











Connector System: Wire-to-Board

Number of Positions: 10

Number of Rows: 2

Centerline (Pitch): 2.5 mm [ .098 in ]
PCB Mount Orientation: Right Angle

### **Features**

### **Product Type Features**

Connector System	Wire-to-Board
Header Type	Fully Shrouded
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
PCB Connector Assembly Type	PCB Mount Header

### **Configuration Features**

Connector Contact Load Condition	Fully Loaded
Number of Positions	10
Number of Rows	2
PCB Mount Orientation	Right Angle

### **Electrical Characteristics**

Operating Voltage	250 VAC

### **Body Features**

Primary Product Color	Natural	



Contact Features	
Mating Pin Diameter	.6 mm[.024 in]
PCB Contact Termination Area Plating Material	Tin
Contact Base Material	Brass
Contact Mating Area Plating Material	Tin
Contact Type	Pin
Contact Current Rating (Max)	7.5 A
Termination Features	
Round Termination Post & Tail Diameter	.6 mm[.024 in]
Termination Post & Tail Length	3.4 mm[.134 in]
Termination Method to Printed Circuit Board	Through Hole - Solder
Mechanical Attachment	
Mating Alignment Type	Polarization
Mating Retention	Without
Panel Mount Feature	Without
Mating Retention Type	Latch
Connector Mounting Type	Board Mount
Mating Alignment	With
PCB Mount Alignment	With
PCB Mount Retention	With
Housing Features	
Housing Material	Nylon
Centerline (Pitch)	2.5 mm[.098 in]
Dimensions	
Connector Length	15.39 mm[.606 in]
Connector Height	12.17 mm[.479 in]
Connector Width	10.16 mm[.4 in]
Row-to-Row Spacing	2.5 mm[.098 in]
Usage Conditions	
Operating Temperature Range	-55 – 105 °C[-67 – 221 °F]
Operation/Application	
Circuit Application	Power & Signal



Industry Standards	
Glow Wire Rating	Standard Part - Not Glow Wire
UL Flammability Rating	UL 94V-0
Packaging Features	

Packaging Quantity	203
Packaging Type	Tray

## **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JUNE 2023 (235) Does not contain REACH SVHC
Halogen Content	Low Halogen - Br, Cl, F, I < 900 ppm per homogenous material. Also BFR/CFR/PVC Free
Solder Process Capability	Wave solder capable to 265°C

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts






# Also in the Series | Economy Power 2.5



Insertion & Extraction Tools(1)



PCB Headers & Receptacles(494)



PCB Latches, Locks & Retainers(49)



Rectangular Power Connectors(43)



Wire-to-Board Connector Assemblies & Housings(311)



Wire-to-Board Connector Contacts(6)

# Customers Also Bought




TE Part #1-2232962-9
9P POTTED RAST 2.5 HEADER



TE Part #1-1969729-0 EP2.5 Shrouded HDR ASSY 10P VERT w/oboss



TE Part #1969729-7 EP2.5 Shrouded HDR ASSY 7P VERT w /o boss



TE Part #6-1971921-7 4/7P,RAST 2.5 Tab Header,Ex- Locking, THV



TE Part #7-1123724-2 03P EP HDR HSG V0 GWT NO 02P



TE Part #1-1969572-2 ASSY, HDR, RIGHT ANGLE, DUAL ROW, EP2.5

TE Part #1-1969729-4
EP2.5 Shrouded HDR ASSY 14P VERT w/oboss

TE Part #1744530-4 EP 2.5 Header no Boss 04P, Red PCB Mount Header, Right Angle, Wire-to-Board, 10 Position, 2.5 mm [.098 in] Centerline, Fully Shrouded, Tin, Through Hole - Solder, Economy Power 2.5



TE Part #1744530-8
EP2.5 HDR ASSY 8P VERT W/O BOSS,

TE Part #2-1744530-4
EP2.5 HDR ASSY 4P VERT W/O BOSS,

### **Documents**

### **Product Drawings**

ASSY, HDR, RIGHT ANGLE, DUAL ROW, EP2.5

English

**CAD Files** 

3D PDF

3D

**Customer View Model** 

ENG\_CVM\_CVM\_1-1969572-0\_A.2d\_dxf.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1969572-0\_A.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_1-1969572-0\_A.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

### Datasheets & Catalog Pages

7-1773461-6\_EP2.5\_Connector\_Series

English

### **Product Specifications**

**Application Specification** 

English

#### **Instruction Sheets**

Instruction Sheet (U.S.)

English

### Agency Approvals

**UL Report** 

English