

PROJECT NAME: \_\_\_\_\_  
 NOTES: \_\_\_\_\_

CAT. #: \_\_\_\_\_  
 FIXTURE SCHEDULE: \_\_\_\_\_

# LED ENCLOSED RATED A-LAMP A19 GU24 BASE GEN 8 SERIES



**6W, 9W, 11W**



**15W**

### Features:

- Omnidirectional LED lamp replicates true A19 incandescents
- 6W, 480lm, 40W Inc. replacement
- 9W, 800lm, 60W Inc. replacement
- 11W, 1100lm, 75W Inc. replacement
- 15W, 1600lm, 100W Inc. replacement
- Dimmable down to 10%
- Suitable for use in fully enclosed luminaires
- Suitable for dry and damp locations

### Base:

- GU24

### Dimming:

- 120V option available with 120V triac dimming (10%)

### Application:

- Pendant
- Table and floor lamp
- Sconces

## Ordering Information

WATTAGE & FAMILY	BASE	DIMMABILITY	COLOR TEMPERATURE	GENERATION
<b>E6A19</b> = 6 Watt, A19 <b>E9A19</b> = 9 Watt, A19 <b>E11A19</b> = 11 Watt, A19 <b>E15A19</b> = 15 Watt, A19	<b>GU</b> = GU24	<b>DLED</b> = Dimmable	<b>27</b> = 2700K <b>30</b> = 3000K <b>40</b> = 4000K <b>50</b> = 5000K	<b>/G8S</b> = Generation 8

## Stocked Items

ORDER CODE	MODEL NUMBER	ENERGY STAR	ORDER CODE	MODEL NUMBER	ENERGY STAR
14099406	E6A19GUDLED30/G8S	2369741	14099410	E9A19GUDLED40/G8S	2370091
14099407	E6A19GUDLED40/G8S	2369742			
104802	E6A19GUDLED50/G8S	2369743			
14099409	E9A19GUDLED30/G8S	2370090			



**5-year standard warranty** (further details available at [www.maxlite.com/warranties](http://www.maxlite.com/warranties))



## LED ENCLOSED RATED A-LAMP

## A19 GU24 BASE GEN 8 SERIES

### Stocked Items

ORDER CODE	MODEL NUMBER	ENERGY STAR	ORDER CODE	MODEL NUMBER	ENERGY STAR
14099411	E11A19GUDLED27/G8S	2370148	14099414	E15A19GUDLED27/G8S	2373415
14099412	E11A19GUDLED30/G8S	2370149	14099415	E15A19GUDLED30/G8S	2373416
14099413	E11A19GUDLED40/G8S	2370150	14099416	E15A19GUDLED40/G8S	2373417
104804	E11A19GUDLED50/G8S	2370151			

### Specifications

Specifications	E6A19GUDLEDxx/G8S	E9A19GUDLEDxx/G8S	E11A19GUDLEDxx/G8S	E15A19GUDLEDxx/G8S
Nominal Wattage	6W	9W	11W	15W
Lumens Delivered	480 lm	800 lm	1100 lm	1600 lm
Equivalency	40W	60W	75W	100W
Efficacy	80 lm/W	89 lm/W	100 lm/W	107 lm/w
Beam Angle	220°			
CRI	≥80			
Color Temperature (K)	2700K, 3000K, 4000K, 5000K			
L70 Lumen maintenance	25,000 Hours			
Power Factor	>0.90		>0.7	
Input Voltage	120V, 60Hz			
Base Type	GU24			
Operating Temperature	-4°F to 104°F (-20 to 40°C)			
Qualifications	cETLus, FCC			
Material Usage	RoHS compliant; no mercury			
Warranty	5 year warranty			

### Compatible Dimmers

DIMMER	MODELS
Lutron	6672, DVCL-1534PR-WH, CTCL-153PDH-WH-C, S-600H-WH-CSA, RDLO6, D-600, TTCL-100
Leviton	6674, DVWCL-153PH, SCL-153PH-WH, 752-DSM10, IPL06