- > multifunctional pliers for electrical installation with 6 functions; to grip flat and round material, for bending, deburring, cutting cable, stripping and crimping ferrules (end sleeves)
- > smooth surfaces near the tips grip single conductors without damaging them; serrated gripping surfaces and pipe grip for gripping flat and round material
- > clear-cut outside edge on the jaw for working on flush-mounted junction boxes and deburring feed-through holes
- > stripping holes for 12 and 14 AWG (0.75 1.5 mm² and 2.5 mm²)
- > crimp die for ferrules (end sleeves) 12 20 AWG (0.5 2.5 mm²)
- > cable shears with induction hardened precision cutting edges for copper and aluminum cables up to 19/32" dia. (5 x 2.5 mm² / dia. 5 mm)
- > slim dimensions for easy access in confined areas
- > bolted joint: precise, zero-backlash operation of pliers
- > high-grade special tool steel; forged, multi stage oil-hardened

13 82 8 T BKA*

Pliers with integrated tether attachment point for tool drop protection system

















| | | | | | | | Cutting capacities | | | | |
|----------------|-----------|-----------------------|----------------------|-----------------------|----------|---|--------------------|-------|---|-------------------------------|------|
| Product Number | Packaging | Inch mm | | Pliers | Head | Handles | Ø Inch | & AWG | Stripping capacities for cross-sections AWG | Crimping capacities AWG | |
| 13 81 8 | X | <mark>8</mark> 200 | | black atramentized | polished | non-slip plastic coated | 9/16 | 0 | 12 and 14 | 12 - 20 | 0.52 |
| 13 82 8 | Х | 8 200 | | black atramentized | polished | multi-component grips | 9/16 | 0 | 12 and 14 | 12 - 20 | 0.59 |
| 13 82 8 T BKA | X | 8 200 | | | | | 9/16 | 0 | 12 and 14 | 12 - 20 | 0.60 |
| 13 88 8 US | X | <mark>8</mark> 200 | ≜ 1000 V ASTM | black atramentized | polished | insulated, multi-component grips, ASTM-tested | 9/16 | 0 | 12 and 14 | 12 - 20 | 0.60 |