

Specification Sheet

Part Number: 156-01797

Low-profile clip attaches easily to plastic and metal edges as thin as 0.5 mm and up to 2.5 mm without the need for a mounting hole. Two designs allow bundles to be secured parallel or vertical to surface edges.

Provides low insertion force and high extraction force – ideal for assembly environments.

Two-piece assembly allows the mount to slide along the strap, ensuring proper orientation.

Cable tie is outside serrated to reduce bundle chafing.



Cable Tie/Edge Clip, 5.7"L, 0.5–2.5 mm Panel, Parallel, 30lb, PA66HS/PA66HIRHS, BK, 500/pkg

Article Number 156-01797

Type T30ROSEC0.5-2.5SP-SVA

Color Black (BK)

Quantity Per bag

Product Description HellermannTyton's Two Piece Edge Clip with Cable Tie Assemblies are designed specifically to route bundles by securing them to the edge of a plastic or metal sheet without the need for a mounting hole. The clip is easy to secure and the extraction force is high due to the integrated metal clamp that holds the edge clip in place.

| | |
|-------------------------------------|---|
| Short Description | Cable Tie/Edge Clip, 5.7"L, 0.5–2.5 mm Panel, Parallel, 30lb, PA66HS/PA66HIRHS, BK, 500/pkg |
| Global Part Name | T30ROSEC0.5-2.5SP-SVA-PA66HS/PA66HIRHS-BK |
| Minimum Tensile Strength (Imperial) | 30.0 |
| Minimum Tensile Strength (Metric) | 133 |
| Length L (Imperial) | 5.7 |
| Length L (Metric) | 145.0 |
| Fixation Method | EdgeClip, sideways, assembled, 2 piece |
| Identification Plate Position | none |
| Variant | Outside Serrated |
| Width W (Imperial) | 0.13 |
| Width W (Metric) | 3.4 |
| Bundle Diameter Min (Imperial) | 0.06 |
| Bundle Diameter Min (Metric) | 1.6 |
| Bundle Diameter Max (Imperial) | 1.38 |
| Bundle Diameter Max (Metric) | 30 |
| Height H (Imperial) | 0.05 |

| | |
|--------------------------------|--|
| Height H (Metric) | 1.2 |
| Panel Thickness Min (Imperial) | 0.01 |
| Panel Thickness Max (Imperial) | 0.1 |
| Panel Thickness Min (Metric) | 0.5 |
| Panel Thickness Max (Metric) | 2.5 |
| Material | Polyamide 6.6, high impact modified, heat stabilized (PA66HIRHS) Polyamide 6.6 heat stabilized (PA66HS) |
| Material Shortcut | PA66HIRHS PA66HS |
| Material Cable Tie | Polyamide 6.6 heat stabilized (PA66HS) |
| Flammability | UL 94 HB |
| UV Resistant (Yes/No) | No |
| Operating Temperature | -40°F to +221°F (-40°C to +105°C) |
| Reach Compliant (Article 33) | Yes |
| ROHS Compliant | Yes |
| Package Quantity (Imperial) | 500 |

Package Quantity (Metric) 500

Customs Number 3926909988

About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

[Contact Us](#)

[RoHS/WEEE Compliance](#)

[Disclaimer](#)

[Terms and Conditions](#)