


7	DATE	REV	ECN	APP'D. BY
	10/15/20	A0	-	ADB
	11/04/20	A1	11655	JE
1				
4				




0.66 [16.8]


HOUSING ASSEMBLY CAP-1(WHITE)


CAP-2(BLACK)

CÀBLE TIE

**ASSEMBLY DIMENSION** 







**SCREW** 


## NOTES:


- 1. SUITABLE FOR USE IN EXISTING CABLE SYSTEMS UP TO CATEGORY 6A PERFORMANCE.
- 2. PHYSICAL HOUSING: ZINC ALLOY, FULLY SHIELDED IDC: PHOSPHOR BRONZE ALLOY WITH 100 µIN TIN PLATING
- 3. ELECTRICAL INSULATION RESISTANCE: 500MOHM MIN. @ 100VDC DIELECTRIC WITHSTANDING VOLTAGE: IEC 60603-7 CONTACT TO CONTACT: 1000 VDC OR AC PEAK
- CONTCT TO SHIELD: 1500 VDC OR AC PEAK 4. MECHANICAL IDC WIRE GAUGE: 22 - 26 AWG, SOLID OR STRANDED

SS-82120-002

PART NUMBER

A SMALLER AWG CANNOT BE USED IN A PREVIOUSLY USED IDC.





a bel group

11118 Susquehanna Trail South Glen Rock, PA 17327-9199 (717) 235-7512

http://www.stewartconnector.com

Α



DRAWING IS SUBJECT TO CHANGE WITHOUT NOTICE

DIMENSIONS: INCHES [METRIC]

UNLESS OTHERWISE SPECIFIED TOLERANCES ARE ±.005 [0.13]
ANGLES ARE ± 1'

SHEET NO. 1 OF ' THIS DRAWING AND THE SUBJECT MATTER SHOWN THEREO ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF

CAT 6A TOOL-LESS CABLE SPLICER

STEWART CONNECTOR AND SHALL NOT BE REPRODUCED, COPIED, OR USED IN ANY MANNER WITHOUT PRIOR WRITTE CONSENT OF STEWART CONNECTOR. ONE OR MORE U.S. PATE MAY APPLY TO THIS PRODUCT. FOR DETAILS, PLEASE VISIT: HTTP://BELFUSE.COM/STEWART/STEWART\_PATENTS

ON )F	DRN BY:			/28/20
, En Ents	APPD BY:	ADB	DATE 10,	/15/20
S/	DWG NO.	CT820036		REV. A1

AutoCAD