



NOTE: 1) IL PRODOTTO VIENE FORNITO IN TUTTI I VOSTRI POCCHI 2) 2) CARATTERISTICHE TECNICHE E FUNZIONALI CONE DA PS 98000.  
 LUNGHEZZA MINIMA DI ESPOSIZIONE DELLE PISTE.  
 3) 3) PRODUCT WILL BE SUPPLIED PREPARED IN A TUBE PER SHEET 200  
 IN TECHNICAL CHARACTERISTICS AS INDICATED IN PRESENT.  
 4) 4) MINIMUM EXPOSED LENGTH OF TRACKS

STD. DESCRIZIONE CON RIL. COM. (Insert contact number) DAT

EC NO. 23000-0077 Class. 5, Rev. 01/23-11-91 C/N. 1/14, Temperature 20-11-91 APPROV. M. No. 1/23-11-91	QUALITY SYMBOLS MAJOR SIGNIF. CRITICAL	GENERAL TOLERANCES UNLESS SPECIFIED DIMENSIONAL TOLERANCES (FRAZ. INCH)	SCALE 5:1 DESIGN UNITS DIMYMM DIMINCH DRAWN BY & DATE BORISCHER 13-04-93 CHECKED BY & DATE APPROVED BY & DATE PAVOLANO 13-04-93 CAD FILENAME 10500008.DWG	FIRST ANGLE PROJECTION TITLE CONNESSIONE PER CIRCUITO FLESSIBILE 81 SPINON 81-003.5 PRESS 2.54 - 198L. SPINONING 1 SPINON 81 SPINON FIT CONTACTOR WITH GOLD TIPS 254 GOLD PEEK PAIR - 800V 1000V 1000V	DIMENSIONAL DIM INCH DIM IN MM DIM INCH DIM IN MM DIM INCH DIM IN MM DIM INCH DIM IN MM
		SHEET NO 1/2	SHEET NO 1/2	MATERIAL NO. SEE SHEET 2	DRAWING NO. 81-98000-008

THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION.

N°. DI CODICE PART. NO.	ATTREZZAGGIO TOOLING	N°. VIE CUT NO.	DIM "A"	DIM "B"	DIM "C"	DIM "D"	N° CONN./TUBO CONN. NO/TUBE	N° CONN./SCATOLA CONN. NO/BOX (SPD)
90500-4102	NON ATTREZZATO NOT TOOLED	2						
90500-4103	"	3						
90500-4104	ATTREZZATO TOOLED	4	22.52	7.62	12.92	12.82	24	3454
90500-4105	"	5	25.06	10.16	15.46	15.36	21	3024
90500-4106	"	6	27.60	12.70	18.00	17.90	19	2736
90500-4107	"	7	30.14	15.24	20.54	20.44	17	2448
90500-4108	"	8	32.68	17.78	23.08	22.98	16	2304
90500-4109	"	9	35.22	20.32	25.62	25.52	15	2160
90500-4110	"	10	37.76	22.86	28.16	28.06	14	2016
90500-4111	"	11	40.30	25.40	30.70	30.60	13	1872
90500-4112	"	12	42.84	27.94	33.24	33.14	12	1728
90500-4113	"	13	45.38	30.48	35.78	35.68	11	1584
90500-4114	"	14	47.92	33.02	38.32	38.22	11	1584
90500-4115	"	15	50.46	35.56	40.86	40.76	10	1440
90500-4116	"	16	53.00	38.10	43.40	43.30	10	1440
90500-4117	"	17	55.54	40.64	45.94	45.84	9	1296
90500-4118	"	18	58.08	43.18	48.48	48.38	9	1296
90500-4119	"	19	60.62	45.72	51.02	50.92	8	1152
90500-4120	"	20	63.16	48.26	53.56	53.46	8	1152

EC MOLEX SHEET 1/2 DRAWN: CHN CHECK: JPN APPROV:	QUALITY SYMBOLS 	GENERAL TOLERANCES UNLESS SPECIFIED <table border="1"> <tr><td></td><td>FINISH</td><td>FINCH</td></tr> <tr><td>4 PLACES</td><td>±0.1</td><td>±.</td></tr> <tr><td>3 PLACES</td><td>±0.1</td><td>±.</td></tr> <tr><td>2 PLACES</td><td>±0.05</td><td>±.</td></tr> <tr><td>1 PLACE</td><td>±0.1</td><td>±.</td></tr> </table>		FINISH	FINCH	4 PLACES	±0.1	±.	3 PLACES	±0.1	±.	2 PLACES	±0.05	±.	1 PLACE	±0.1	±.	SCALE: 5:1 DESIGN UNITS: DIMM INCH DRAWN BY & DATE: Bortolotto 13-04-93 CHECKED BY & DATE: APPROVED BY & DATE: Paganelli 13-04-93 CAD FILENAME: 90500008_001	DIMENSIONS: <input type="checkbox"/> DIM INCH <input type="checkbox"/> DIM FEET <input type="checkbox"/> DIM MM ONLY <input type="checkbox"/> DIM INCH ONLY	SHEET REV REVISE ON CAD ONLY 2/2 A.1
		FINISH	FINCH																	
4 PLACES	±0.1	±.																		
3 PLACES	±0.1	±.																		
2 PLACES	±0.05	±.																		
1 PLACE	±0.1	±.																		
CRITICAL 	DIMENSIONS WHERE APPLICABLE MUST REMAIN WITH DIMENSIONS	FIRST ANGLE PROJECTION 	TITLE: CONNETTORE PER CEMENTO FLESSIBILE 81 SPINON N°4x3 E PRESS 2.54x1.27. SPINONDA 1 SPINONDA 8 PINN 1/2 CONNETTORE PER CEMENTO FLESSIBILE 254x127 PER PROF - 4004 MOLEX 90500 -	MATERIAL NO. SEE TABLE	DRAWING NO. 90-9000-008															