1.5 METERS LENGTH






Connector A 901-9872 SMA Plug Right Angle Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot

Connector B 919-387P-51A MCX Plug Right Angle Brass Gold-Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed \sim 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.



Connector A			Cable		Connector B	
Part #:	901-9872	Part #:	RG-174	Part #:	919-387P-51A	
Description:	SMA R/A PLUG RG174 500	Description:	RG-174 - PE 0.1	Description:	MCX R/A PLUG RG174 RG188 RG316 500	
Type:	SMA	Dielectric:	PE	Type:	MCX	
Gender:	Plug	Shielding:	Braid	Gender:	Plug	
Body Type:	Right Angle	Diameter:	0.1	Body Type:	Right Angle	
Contact Type:	Solder	Impedance:	50 Ohm	Contact Type:	Solder	
Polarity:	Standard	Sheathing:	None	Polarity:	Standard	
Impedance:	50 Ohm	Testing:	Continuity Hi-Pot	Impedance:	50 Ohm	
Mounting:	Cable	Length:	1.5 Meters	Mounting:	Cable	
Body Material:	Brass			Body Material:	Brass	
Body Finish:	Gold			Body Finish:	Gold-Nickel	
IP Rating:	None			IP Rating:	None	
Contact Material:	Brass			Contact Material:	Brass	
Contact Finish:	Gold			Contact Finish:	Gold	
Max. Freq.:	12.4 GHz			Max. Freq.:	6 GHz	
Booting:	SMA Plug Right Angle			Booting:	MCX Plug Right Angle	
-				Clocking:	0°	



CONTROLLED DOCUMENT - DO NOT COPY

THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTEN CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.

SMA-RA-PL/MCX-RA-PL G174 1.5M

Q-3401A00031.5M

UNLESS SPECIFIED

TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES