

**RIDERSERIES  
SRC CLIP HM**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 16  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Weidmüller RIDERSERIES relays guarantee a noise-free, decoupled signal transmission in industrial automation concepts. Quickly mounted, they are compact and can be integrated in the tightest of spaces.

- 1 NO contact
- 1 or 2 CO contacts
- With either hard gold-plated 1 or 2 CO contacts
- Low height of 15.7 mm
- AC / DC coils
- Screw / PUSH-IN wire connection

**General ordering data**

Order No.	<a href="#">8693370000</a>
Type	SRC CLIP HM
Version	RIDERSERIES, Retaining clip
GTIN (EAN)	4032248364817
Qty.	10 pc(s).

**RIDERSERIES  
SRC CLIP HM**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

Net weight 400 g

**Temperatures**

Humidity	40 °C / 93 % rel. humidity, no condensation	Operating temperature	-40 °C...+70 °C
Storage temperature	-40 °C...+85 °C		

**general data**

Humidity 40 °C / 93 % rel. humidity,  
no condensation

**Insulation coordination**

Protection degree IP 20

**Other technical data**

Version Relay accessories

**Classifications**

ETIM 2.0	EC001456	UNSPSC	30-21-19-17
eClass 4.1	27-37-11-90	eClass 5.1	27-37-16-03
eClass 6.2	27-37-16-03	eClass 7.1	27-37-16-03

**Approvals**

Approvals



**RIDERSERIES  
SRC CLIP HM**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 16  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Mating connector (fully pluggable)**

**Base**



- Coupling relay with positively driven contacts: for monitoring signals within safety-critical circuits
- Relays with positively driven contacts have a 99% diagnostics coverage and an excellent reputation for use in safety systems.
- The contacts interlock with each other in order to ensure a synchronous switching status between both contacts. This guarantees that the alert contact will maintain the same switching status in the event of an error (for example, if the working contact melts from an overload).

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">8783930000</a>	SRC 2CO Z	RIDERSERIES, Relay base, Tension clamp connection	4032248471430	10 pc(s).
<a href="#">8690830000</a>	SRC 2CO	RIDERSERIES, Relay base, Screw connection	4032248361519	10 pc(s).

**Base**



Relay base for RIDERSERIES RCL relays

- Screw and tension clamp connection
- Standard and low heights
- Plug-in frame for PCB connections

**General ordering data**

Order No.	Type	Version	GTIN (EAN)	Qty.
<a href="#">8693930000</a>	SRC 2CO N	RIDERSERIES, Relay base, Screw connection	4032248365418	10 pc(s).