



**CORE DIMENSIONS** **28T0301-000**

UNCOATED CORE					
	MM	INCHES		MM	INCHES
OD	7.62	(.300)	±	.15	(.006)
ID	3.18	(.125)	±	.13	(.005)
TH	4.78	(.188)	±	.13	(.005)

**SINGLE PARAYLENE** **28T0301-00P**

OD	7.65	(.301)	±	.15	(.006)
ID	3.15	(.124)	±	.13	(.005)
TH	4.80	(.189)	±	.13	(.005)

WEIGHT / K 0.8773 KGS 1.9341 LBS  
 INITIAL PERMEABILITY **850**

**ROOM TEMPERATURE ELECTRICAL SPECIFICATION**

	MIN. TOL.	MIN. (μH)	NOM. (μH)	MAX. (μH)	MAX. TOL.	FREQ. (kHz)	VOLT. (mV)	GAUSS	TURNS
L1-1T	-20.0%	0.569	0.711	0.853	20.0%	100	4.42	10	1
Q		Ref.				100	4.42	10	1
NET IMPEDANCE	MIN (Ω)	MIN TOL.	NOM (Ω)			FREQ. (MHz)			TURNS
Z1 (REF.)	22.46	(-25 %)	29.94	-	-	25			1
Z2	42.42	(-25 %)	56.6	-	-	150			1

**COATING SPECIFICATIONS**

TYPE	Max. Coating (mm / mils.)	Min. DLB VAC	TEST FORCE (LB)
Paraylene	(0.0127 / 0.5)	1000	.58

NOTES:



Rev	Description	Date	INT
A	Original Draft	2009-7-7	Jcai

Date: 2009-7-7	DWG # 28T0301-00P-A	Rev: A
Drawn By: Jcai	Title # 28T0301-00P	

Steward This document contains information which is proprietary to Steward. No production or publication of this document in whole or in part shall be made without written authorization from Steward.

UNCONTROLLED DOCUMENT