

SPE-T1-STRM-90 - SPE PCB connector



1163797

<https://www.phoenixcontact.com/us/products/1163797>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



SPE PCB connector, design: IEC 63171-2, degree of protection: IP20, number of positions: 2, 1 Gbps, CAT B (ISO/IEC 63171), material: Metal, connection method: THR solder connection, cable outlet: straight, Single Pair Ethernet

Your advantages

- Compact design for maximum space savings
- Connectors in accordance with IEC 63171-2
- THR solderable
- Robust industrial design
- 360° shielding
- Data transmission up to 600 MHz

Commercial data

Item number	1163797
Packing unit	1 pc
Minimum order quantity	100 pc
Sales key	AB13
Product key	ABNBDA
GTIN	4063151175979
Weight per piece (including packing)	4.14 g
Weight per piece (excluding packing)	3.96 g
Customs tariff number	85366990
Country of origin	DE

SPE-T1-STRM-90 - SPE PCB connector



1163797

<https://www.phoenixcontact.com/us/products/1163797>

Technical data

Product properties

Type	SPE
Product type	Data connector (device side)
Sensor type	Single Pair Ethernet
Number of positions	2
Type of packaging	Tape and Reel
Pitch	7.62 mm
Connection profile	SPE
Number of slots	1
Type	Socket
Shielded	yes
Cable outlet	straight

Insulation characteristics

Overvoltage category	II
Degree of pollution	2

Electrical properties

Rated voltage (III/2)	72 V DC
Rated surge voltage	2250 V DC
Rated surge voltage (III/2)	1500 V
Rated current	4 A
Frequency range	600 MHz
Insulation resistance	> 1 TΩ
Transmission medium	Copper
Transmission speed	1 Gbps
Power transmission	PoDL

Connection data

Connection technology

Connection method	THR solder connection
-------------------	-----------------------

Dimensions

Width	5 mm
Height	8.35 mm
Length	14.2 mm

Material specifications

Flammability rating according to UL 94	V0
Contact material	Copper alloy
Contact surface material	Ni/Au
Contact carrier material	LCP

SPE-T1-STRM-90 - SPE PCB connector



1163797

<https://www.phoenixcontact.com/us/products/1163797>

Housing material	Metal
------------------	-------

Cable/line

Test voltage Core/Core	1000 V DC
Test voltage Core/Shield	2250 V DC
Halogen-free	yes
Resistance to oil	yes
Flame resistance	UL 94 V0

Mechanical properties

Mechanical data

Insertion/withdrawal cycles	≥ 750
Insertion force per signal contact	< 1.50 N
Extraction force per signal contact	< 1.5 N

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Resistance to oil	yes

Standards and regulations

Flame resistance	UL 94 V0
Resistance to oil	yes

Mounting

Mounting type	THR soldering
Connection method	THR solder connection

Processing notes

Moisture Sensitive Level	MSL 1
--------------------------	-------

SPE-T1-STRM-90 - SPE PCB connector




1163797

<https://www.phoenixcontact.com/us/products/1163797>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1163797>

 cULus Recognized Approval ID: E335024-20220331				
	Nominal voltage U_N	Nominal current I_N	Cross section AWG	Cross section mm^2
	60 V	1.4 A	-	-

SPE-T1-STRM-90 - SPE PCB connector



1163797

<https://www.phoenixcontact.com/us/products/1163797>

Classifications

ECLASS

ECLASS-11.0	27440390
ECLASS-13.0	27440390
ECLASS-12.0	27440390

ETIM

ETIM 8.0	EC001121
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

SPE-T1-STRM-90 - SPE PCB connector



1163797

<https://www.phoenixcontact.com/us/products/1163797>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e No hazardous substances above threshold values
------------	---

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com