


NOTES:

1. HOOD: PBT GF UL 94 V0
2. SCREW 4-40 UNC: STEEL; NICKEL PLATED
3. SCREW FOR STRAIN RELIEF: STEEL; NICKEL PLATED
4. COVER SCREW: STEEL; NICKEL PLATED
5. STRAIN RELIEF: STEEL; NICKEL PLATED
6. FEMALE CONNECTOR 7W2, CRIMP STYLE WITH WIRE BRIDGE AWG 22
SIGNAL CONTACTS: COPPER ALLOY; 7,5A nominal
PLATING: 30µin HARD GOLD over min. 50µin NICKEL
FEMALE CONTACTS WIRE BRIDGE FROM POS. 1 TO POS. 2

<p>POS. 1</p>  <p>2x SCREW 4-40 UNC with allen wrench head</p>	<p>POS. 2</p>  <p>1x CABLE STRAIN RELIEF</p>
<p>POS. 3</p>  <p>2x COVER SCREW</p>	<p>POS. 4</p>  <p>2x CABLE STRAIN RELIEF SCREW</p>

APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION. OWNERSHIP AND COPYRIGHT OF CONEC GmbH			
DO NOT ALTER CAD DRAWING BY HAND			
rev.	description	date	name
a	Origin		

tolerance ISO 2768-m	dim. in mm	scale: 2:1
		material: see notes
title: PLASTIC HOOD, straight cable exit with 7W2 Female Crimp Connector with wire bridge		
dwg no:	Inventor 10	DIN-A3
	13K1A2544	sh: 1
part no:	13-000231	

