

4

3

2

1

THIS DRAWING IS UNPUBLISHED. RELEASED FOR PUBLICATION
 © COPYRIGHT - By - ALL RIGHTS RESERVED.

LOC	DIST	REVISIONS			
P	LTR	DESCRIPTION	DATE	DWN	APVD
H	-	F	PER ECR-12-019004	1NOV12	D.S A.C

CONNECTOR ASSEMBLY EXEMPLARY LOADED

CONTACT DIMENSIONS

RECOMMENDED PCB-HOLE LAY-OUT COMPONENT SIDE SHOWN

CONTACT LAYOUT

	a	b	c	d	e
1	1	1	1	1	1
2	1	1	1	1	1
3	1	1	1	1	1
4	1	1	1	1	1
5	1	1	1	1	1
6	1	1	1	1	1
7	1	1	1	1	1
8	1	1	1	1	1
9	1	1	1	1	1
10	1	1	1	1	1
11	1	1	1	1	1
12	1	1	1	1	1
13	1	1	1	1	1
14	1	1	1	1	1
15	1	1	1	1	1
16	1	1	1	1	1
17	1	1	1	1	1
18	1	1	1	1	1
19	1	1	1	1	1

P.C.B. HOLE DIM. ACTION PIN
FOR DETAILS SEE
APPLICATION SPECIFICATION

NOTES:

- MATERIAL HOUSING : GREY GLASSFILLED POLYESTER
CONTACT : COPPER ALLOY
- GENERAL PLATING SPECIFICATION: UNDERPLATING (ENTIRE CONTACT): 1,27µm NICKEL MIN.
AND ACTION PIN: 0,5µm TIN-LEAD MIN.
FOR PLATING OF MATING SURFACES SEE APPLICABLE SPECIFICATION REFERENCE FOR EACH DASH NUMBER.
- CONFORMS TO ALL TESTING ACCORDING TO IEC 61076-4-101 PERFORMANCE LEVEL 2.
- CONNECTOR TESTED AND QUALIFIED AGAINST TELCORDIA GR-1217-CORE QUALITY LEVEL III, CENTRAL OFFICE APPLICATIONS.
- CONNECTOR LUBRICATED WITH TELCORDIA GR-1217-CORE APPROVED LUBRICANT.
- CONNECTOR MARKED WITH PARTNUMBER AND DATECODE
- PLATED-THROUGH HOLES AT 2x2mm SQUARE GRID.
- HOLES IN ROW f POSSIBLE FUTURE USE OF GROUND RETURN SHIELDS. (NOT YET TOOLED)
- OBSOLETE PARTS: OBSOLETE CIS STREAMLINING PER D.RENAUD/D.SINISI
- 0,76µm MIN. GOLD PLATING AT MATING SURFACES.

CONTACT FINISH	PARTNUMBER
3	3-352406-0
4	352406-9
5	352406-1

THIS DRAWING IS A CONTROLLED DOCUMENT.		DWN	21MAR98	TE Connectivity	
DIMENSIONS: mm		CHK	L.v.d.HEIJDEN	Z-PACK 2MM HM TYPE B19	
TOLERANCES UNLESS OTHERWISE SPECIFIED:		APVD	D. TRUREN	95 POS. RIGHT ANGLE MALE	
Ø PLG ±		PRODUCT SPEC	F.V.KONINGSBRUGGE	CONNECTOR ASSEMBLY	
1 PLG ±		APPLICATION SPEC	108-19082	SIZE	A2
2 PLG ± ±0.20		WEIGHT	114-19029	CAGE CODE	00779
3 PLG ±		FINISH	SEE TABLE	DRAWING NO	C=352406
4 PLG ±				RESTRICTED TO	-
ANGLES ±				SCALE	NTS
MATERIAL				SHEET	1 of 1
FINISH				REV	F
SEE TABLE					

1471-9 (3/11)

352406

A