


EMD-SL-PS- 24DC

Order No.: 2885359



<http://eshop.phoenixcontact.de/phoenix/treeViewClick.do?UID=2885359>

Power modules, pluggable, for EMD-SL-..., supply voltage: 20 V DC ... 30 V DC

Commercial data	
GTIN (EAN)	4 046356 049887 
sales group	H290
Pack	1 pcs.
Customs tariff	85043180
Catalog page information	Page 652 (IF-2009)

Product notes

WEEE/RoHS-compliant since:
12/03/2009



<http://www.download.phoenixcontact.com>
Please note that the data given here has been taken from the online catalog. For comprehensive information and data, please refer to the user documentation. The General Terms and Conditions of Use apply to Internet downloads.

Technical data	
Input data	
Nominal input voltage	24 V DC
DC input voltage range	20 V DC ... 30 V DC
General data	
Width	32 mm

Height	35 mm
Depth	16 mm
Ambient temperature (operation)	-25 °C ... 55 °C
Ambient temperature (storage/transport)	-25 °C ... 70 °C

Address

PHOENIX CONTACT Inc., USA
586 Fulling Mill Road
Middletown, PA 17057, USA
Phone (800) 888-7388
Fax (717) 944-1625
<http://www.phoenixcon.com>



© 2011 Phoenix Contact
Technical modifications reserved;