





19" Desktop Touch Monitor

Effortless Multi-Touch Experience

Projected Capacitive touch technology provides a smooth, effortless multi-touch experience—identical to many of your favorite mobile touch devices.

Greater Durability

Optically bonded cover glass provides a highly durable surface for longer, trouble-free service life.

Display Details

M19A-1101
19.0″ TFT - Active Matrix
376.3 H x 301.1 V mm
WLED
5:4
1280 x 1024
16.7 M (6 bits + Hi-FRC)
0.294 H x 0.294 V mm
225 cd/m ²
1000:1
170°
160°
5 ms

Touch Details

Touch Technology	Projected Capacitive
Multi-Touch Input	2 points
Input Method	Finger, Thin Glove
Touch Interface	USB-Туре В
Multi-Touch OS Support	Windows 7/8/10 & Linux - Native HID
Single-Touch OS Support	All Windows, Linux & Mac OSX

Dimensions and Weight

Display (WxHxD)	438.7 x 408.1 x 267.4 mm
Display Weight	8.0 Kg
Shipping Weight	10.8 Kg

Sophisticated Bezel-Free Design

Smooth multi-touch surface across the entire face of the monitor for refined aesthetics and easy cleanability.

Product Details

Power Supply	100 - 240V AC or 12V DC, 4.16A
Power Consumption	Operating: 20W Sleep: 3W Off: 1W
Video Input	Analog VGA, DVI-D
Audio Input	Built-in 1W / 2 Channel Speakers
Mounting Options	VESA Mount, Included Stand
VESA Pattern	100 x 100 mm
Operating Conditions	0°C to +40°C, Noncondensing 80%
Storage Conditions	-20°C to +60°C, Noncondensing 90%
Agency Approvals	TUV, CE, UL, CUL, FCC-B, RoHS
Warranty	3 year

The information presented in this specification sheet is intended as general information about TPK America, LLC products and is subject to change. Product specifications and warranties will be governed by TPK America, LLC standard terms and conditions of sale. Products are subject to availability. 100417R1

