



ナイロン66, 94V-0  
 NYLON66, 94V-0  
 色: オフホワイト  
 COLOR: OFF WHITE

注)  
 NOTE.

△ フリクションロック構成:  
 FRICTION LOCK CONFIGURATION:  
 4極までは1箇所  
 4CKT AND UNDER - 1LOCK  
 5極以上は2箇所  
 5CKT AND OVER - 2LOCKS

2. 嵌合相手: 5102-N  
 MATES WITH HOUSING: 5102-N

△ スリット構成:  
 SLIT CONFIGURATION:  
 4極以下はなし  
 4CKT AND UNDER - NO SLIT  
 5及び6極は1箇所  
 5 AND 6CKTS - 1 SLIT  
 7極以上は2箇所  
 7CKT AND OVER - 2 SLITS

29-11-0153	5240-151	35	38.7	41.1	5	38.3	15
↑ -0143	↑ -141	32.5	36.2	38.6	5	35.8	14
-0133	-131	30	33.7	36.1	5	33.3	13
-0123	-121	27.5	31.2	33.6	5	30.8	12
-0103	-101	22.5	26.2	28.6	5	25.8	10
-0093	-091	20	23.7	26.1	5	23.3	9
-0083	-081	17.5	21.2	23.6	5	20.8	8
-0073	-071	15	18.7	21.1	5	18.3	7
-0063	-061	12.5	16.2	18.6	5	15.8	6
-0053	-051	10	13.7	16.1	3.75	13.3	5
-0043	-041	7.5	11.2	13.6	7.5	10.8	4
↓ -0033	↓ -031	5	8.7	11.1	5	8.3	3
29-11-0023	5240-021	2.5	6.2	8.6	2.5	5.8	2
EDP.NO.	ENG.NO.	B	C	(A)	(E)	(D)	極数 CKT.

REVISED EC NO: J2016-0727 DRWN: SNAKAMURA08 2016/01/20 CHKD: KASAKAWA 2016/02/12 APPR: IKANEKO 2016/02/26	GENERAL TOLERANCES (UNLESS SPECIFIED)			DIMENSION STYLE MM ONLY		SCALE 2:1	DESIGN UNITS METRIC	THIRD ANGLE PROJECTION
	0.25 UNDER	UNDER	±0.2	DRAWN BY KKOHAYA	DATE 2000/01/28	TITLE MINI. SPOX PLUG HSG		
	0.25 OVER	0.5 UNDER	±0.2	CHECKED BY TYAMAGUCHI	DATE 2000/03/30			
	0.5 OVER	1.0 UNDER	±0.2	APPROVED BY				
	1.0 OVER	10 UNDER	±0.2	MATERIAL NO. SEE CHART		DOCUMENT NO. SD-5240-N1	SHEET NO. 1 OF 1	
10 OVER	30 UNDER	±0.25	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX ELECTRONIC TECHNOLOGIES, LLC AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION			