

Touch panel - TP 12T - 2985194

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Touch panel with 30.7 cm (12.1") graphics-capable TFT display, 65,535 colors, 800 x 600 pixels, 1 x Ethernet, 2 x USB, and integrated runtime of the Visu+ visualization software.

Product Features

- Short startup time
- Easy installation, low installation depth, and compact design
- Display available in sizes from 8.9 cm (3.8") to 38.1 cm (15")
- Visu+ RT and AX OPC server integrated as standard in all devices
- Energy efficient due to LED backlighting

Key commercial data

| | |
|--------------------------------------|------------|
| Packing unit | 1 pc |
| Weight per Piece (excluding packing) | 3465.0 GRM |
| Custom tariff number | 84714100 |
| Country of origin | Germany |

Technical data

Note

| | |
|-------------------------|---|
| Utilization restriction | EMC: class A product, see manufacturer's declaration in the download area |
|-------------------------|---|

Dimensions

| | |
|-----------------------------------|-------------------------------|
| External dimension, width | 340 mm |
| External dimension, height | 270 mm |
| External dimension, depth | 5 mm |
| Note regarding external dimension | Dimensions of the front plate |
| Installation dimension, width | 315 mm |
| Installation dimension, height | 243.5 mm |

Display

| | |
|------------|------------------------|
| Display | 30.7 cm/12.1" TFT |
| Resolution | 800 x 600 Pixel (SVGA) |

Touch panel - TP 12T - 2985194

Technical data

Display

| | |
|--------------|-----------------------------------|
| Backlighting | LED |
| Touch screen | Resistive industrial touch screen |
| Colors | 65,536 colors |

Computer data

| | |
|-------------------|------------------------------------|
| Processor | Xscale® PXA320, 806 MHz |
| RAM | 128 MB SDRAM |
| Mass storage | 1 GB Flash |
| Interfaces | 2x USB Host 1.1, 1x Compact Flash® |
| Network | 1 x Ethernet (10/100 Mbps), RJ45 |
| Operating systems | Windows CE 5.0 |

General

| | |
|---------------|-----------------------------|
| Mounting type | Installation in front plate |
|---------------|-----------------------------|

Ambient conditions

| | |
|--|--------------------------------|
| Degree of protection | IP65 (front), IP20 (back) |
| Ambient temperature (operation) | 0 °C ... 50 °C |
| Ambient temperature (storage/transport) | -25 °C ... 70 °C |
| Permissible humidity (operation) | 20 % ... 85 % (non-condensing) |
| Permissible humidity (storage/transport) | 10 % ... 95 % (non-condensing) |
| Vibration (operation) | DIN EN 60068-2-6 |
| Shock | DIN EN 60068-2-27 |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27330202 |
| eCl@ss 4.1 | 27330202 |
| eCl@ss 5.0 | 27242215 |
| eCl@ss 5.1 | 27242301 |
| eCl@ss 6.0 | 27242301 |
| eCl@ss 7.0 | 27242301 |
| eCl@ss 8.0 | 27242301 |

ETIM

| | |
|----------|----------|
| ETIM 2.0 | EC001426 |
| ETIM 3.0 | EC001426 |
| ETIM 4.0 | EC001426 |

Touch panel - TP 12T - 2985194

Classifications

ETIM

| | |
|----------|----------|
| ETIM 5.0 | EC001414 |
|----------|----------|

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 43172015 |
| UNSPSC 7.0901 | 43201404 |
| UNSPSC 11 | 43172015 |
| UNSPSC 12.01 | 43211903 |
| UNSPSC 13.2 | 43201404 |

Approvals

Approvals


Approvals

UL Listed / cUL Listed / GL / BV / ABS / GL-SW / GL / cULus Listed

Ex Approvals

Approvals submitted

Approval details

| |
|---|
| UL Listed  |
|---|

| |
|--|
| cUL Listed  |
|--|

| |
|----|
| GL |
|----|

| |
|----|
| BV |
|----|

| |
|-----|
| ABS |
|-----|

Touch panel - TP 12T - 2985194

Approvals

GL-SW

GL

cULus Listed 