



## Specifications

### Characteristic

#### Main characteristics

Category (TIA/EIA)	5e
Number of ports	24
Mounting height	1U
Patch panel type	whole
Port Type	RJ45 (8P8C)
Color	black

#### Dimensions and weight

Height, mm	44
------------	----

#### General characteristics

Permissible conductor gauge	26-22 AWG
Port labeling	digital marking
Wiring diagram	T568B
Type of IDC contacts	Dual IDC

### Electrical characteristics

Insulation test voltage	1000 V / 60 Hz / 1 min.
-------------------------	-------------------------

Contact resistance (max.)	20 mΩ
---------------------------	-------

Insulation resistance (min.)	500 MΩ
------------------------------	--------

### Materials

IDC contact material	tin plated phosphor bronze
----------------------	----------------------------

PCB contact material	phosphor bronze with gold plating
----------------------	-----------------------------------

Housing material of the IDC module	polycarbonate (PC)
------------------------------------	--------------------

Housing material	sheet steel 1.6 mm
------------------	--------------------

Printed circuit board (PCB) material	4-layer fiberglass (FR-4) 1.6 mm
--------------------------------------	----------------------------------

PCB connector material	polybutylene terephthalate (PBT), glass fiber reinforced
------------------------	--

Shield cover material	cold-rolled sheet steel 1.0 mm
-----------------------	--------------------------------

### Ordering

PP-19-24-8P8C-C5E-SH-110D	Patch Panel 19" 24 Ports RJ45 Cat 5e 110 IDC Shielded
---------------------------	---