



- A. Constructed of a lightweight dissipative material which is made from texturized polyester and a minimum of 9% carbon nylon monofilament*
Can be washed multiple times in a mild detergent**.
- B. A nose wire helps ensure mask fits securely
- C. Elastic bands range from Small-Medium (2.75") to Large-Extra Large (3.25").
The mask area is the same size for all items. (D x E)

Specifications

Fabric Weight* 2.2 oz per square yard
 Fabric Content Texturized polyester and a minimum of 9% carbon mono-filament nylon.
 Carbon Mono-filament Conductive at 1×10^4 ohms, nonflaking and non-sloughing.
 Surface Resistance $1 \times 10^5 < 1 \times 10^7$ ohms, per ANSI/ESD STM2.1 and ESD TR53 of Fabrics
 Glass Transition Temp 250°F
 Flash Point 1040°F

*Fabric lots vary slightly in color and weight.

Mask Selection		
Item #	Color	Strap Size
97550	Blue	Small-Medium
97551	White	Small-Medium
97552	Gray	Small-Medium
97553	Blue	Large-Extra Large
97554	White	Large-Extra Large
97555	Gray	Large-Extra Large

****Mask Laundering**

The mask should be laundered periodically. Woolite works well. Liquid detergents are better than dry in that there is less caking and frictional wear. Launder mask in cool or warm water, tumble dry with low heat or hang dry. Machine washing works well if using a standard house machine on gentle cycle. It is not recommended to launder these masks in heavy industrial laundry machines as it will lead to premature wear. Masks should be tumbled dry using low heat. DO NOT BLEACH. After laundering, verify (Rgp) $< 1 \times 10^7$ ohms.

Unless otherwise noted, tolerance $\pm 1/2"$



Made in the United States of America

STATIC DISSIPATIVE FACEMASKS

DESCO

DESCO WEST: 3651 WALNUT AVE, CHINO, CA 91710 WEBSITE: Desco.com
 PHONE: (909) 627-8178

DESCO EAST: ONE COLGATE WAY, CANTON, MA 02021-1407
 PHONE: (781) 821-8370

DRAWING NUMBER
97550

DATE:
December 2020