

# REL-SW230/F104 - Single relay



2960193

<https://www.phoenixcontact.com/us/products/2960193>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



KAMMRELAIS®, contact F 104, size 2, heavy-duty contact, 2 changeover contacts, 230 V AC

## Commercial data

Item number	2960193
Packing unit	1 pc
Minimum order quantity	1 pc
Note	Made to order (non-returnable)
Sales key	C460
Product key	CK6192
Catalog page	Page 103 (IF-2002)
GTIN	4017918086602
Weight per piece (including packing)	39.22 g
Weight per piece (excluding packing)	35.266 g
Customs tariff number	85364900
Country of origin	DE

# REL-SW230/F104 - Single relay



2960193

<https://www.phoenixcontact.com/us/products/2960193>

## Technical data

### Product properties

Product type	Single relay
Mechanical service life	approx. 10 <sup>6</sup> cycles

### Electrical properties

Test voltage (Winding/contact)	1 kV AC (50 Hz, 1 min., winding/contact)
Test voltage (Changeover contact/changeover contact)	1 kV AC (50 Hz, 1 min., changeover contact/changeover contact)

### Input data

#### Coil side

Nominal input voltage $U_N$	230 V AC
Input voltage range	184 V AC ... 243.8 V AC
Input voltage range in reference to $U_N$	0.8 ... 1.06
Typical response time	4 ms ... 15 ms
Typical release time range	4 ms ... 15 ms
Coil resistance	14000 $\Omega$ $\pm$ 15 %

### Output data

#### Switching

Contact switching type	2 changeover contacts
Type of switch contact	Single contact
Contact material	Ag, gold-flashed
Maximum switching voltage	250 V AC/DC
Limiting continuous current	5 A
Maximum inrush current	5 A
Interrupting rating (ohmic load) max.	120 W (at 24 V DC) 60 W (at 48 V DC) 50 W (at 60 V DC) 70 W (at 110 V DC) 70 W (for 250 V DC) 500 VA (for 250 V AC)

### Connection data

Connection method	Plug-in connection
-------------------	--------------------

### Environmental and real-life conditions

#### Ambient conditions

Ambient temperature (operation)	-40 °C ... 70 °C
Ambient temperature (storage/transport)	-40 °C ... 70 °C

# REL-SW230/F104 - Single relay

2960193

<https://www.phoenixcontact.com/us/products/2960193>



## Classifications

### ECLASS

ECLASS-11.0	27371601
-------------	----------

# REL-SW230/F104 - Single relay



2960193

<https://www.phoenixcontact.com/us/products/2960193>

## Environmental product compliance

China RoHS	Environmentally Friendly Use Period = 5 For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"
------------	---

Phoenix Contact 2023 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)