

Data sheet | Item number: 2065-131

Board-to-Board Link; Pin spacing 6.5 mm; Length: 15.6 mm; silver-colored

www.wago.com/2065-131



Color:



Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



Item description

- Board-to-board links simplify in-line assembly of LED modules
- Space saving connection of PCBs

Data

Notes

Safety information

Subject to changes. Please also observe the further product documentation!

**Notice:**

Terminal block without insulation housing! Protection against accidental contact must be provided at voltages higher than low voltages (e.g., SELV/PELV) for the relevant application.

Note	The layout must meet the requirements of the insulation coordination standard EN/IEC 60664-1 and applicable end product standards. When using board-to-board links, please note the potentially reduced clearances (e.g., with metal core boards).
------	--

Electrical data**Ratings per IEC/EN**

Ratings per	IEC/EN 60664-1
Nominal voltage (III/3)	250 V
Rated impulse voltage (III/3)	4 kV
Rated voltage (III/2)	320 V
Rated impulse voltage (III/2)	4 kV
Nominal voltage (II/2)	630 V
Rated surge voltage (II/2)	4 kV
Rated current	9 A
Legend (ratings)	(III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2

Physical data

Depth	15.6 mm / 0.614 inches
Length	15.6 mm
Diameter	1 mm

Mechanical Data

Mating cycles (max.)	10
Number of mating cycles	10 connections/disconnections (max.)
Suitable	for SMD PCB terminal blocks; 2065 Series

Material Data

Note (material data)

Information on material specifications can be found here

Subject to changes. Please also observe the further product documentation!



Color	silver-colored
Contact material	Copper alloy
Contact plating	Silver
Weight	0.1 g

Environmental requirements

Limit temperature range	-60 ... +120 °C
-------------------------	-----------------

Commercial data

ETIM 8.0	EC002848
ETIM 7.0	EC002848
PU (SPU)	1500 pcs
Packaging type	box
Country of origin	DE
GTIN	4055143862721
Customs tariff number	85369010000

Environmental Product Compliance

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

Counterpart

Item no.2065-100/998-403 SMD PCB terminal block; push-button; 0.75 mm ² ; Pin spacing 6.5 mm; 1-pole; Push-in CAGE CLAMP®; in tape-and-reel packaging; Without housing; 0,75 mm ² ; silver-colored	www.wago.com/2065-100/998-403
Item no.2065-101/998-403 SMD PCB terminal block; 0.75 mm ² ; Pin spacing 6 mm; 1-pole; PUSH WIRE®; in tape-and-reel packaging; Without housing; 0,75 mm ² ; silver-colored	www.wago.com/2065-101/998-403

Downloads**Documentation****Additional Information**

2019 年4月3日

pdf
2.0 MB

Download

CAD/CAE-Data**CAD data**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



2D/3D Models 2065-131

[URL](#)

[Download](#)

CAE data

ZUKEN Portal 2065-131

[URL](#)

[Download](#)

Environmental Product Compliance

Compliance Search

Environmental Product Compliance 2065-131

[URL](#)

[Download](#)

Board-to-Board Link; Pin spacing 6.5 mm; Length: 15.6 mm; silver-colored

Installation Notes

Installation



Insert the board-to-board links into the terminal blocks.


Installation

Subject to changes. Please also observe the further product documentation!



Assembly: Place PCBs on a flat surface and insert links into terminal blocks on adjoining PCBs. Disassembly: Open the terminal blocks with an operating tool. (max. 5 connections /disconnections)

Installation



The PCBs must be secured.

Subject to changes. Please also observe the further product documentation!