


# Harting Grey Plastic Cable Seals



Material  
Seal  
Protection  
(DIN 40050)  
Operating  
temperature

Polyamide self-extinguishing  
Buna-N  
IP 68 - 10 bar (150 PSIG)  
within the specified clamping range  
static -40° C to 100° C, (-40° F to 212° F),  
short time exposure 120° C (248° F)  
dynamic -20° C to 80° C, (-4° F to 176° F),  
short time exposure 100° C (212° F)

| <b><i>Part<br/>Number</i></b> | <b><i>AG<br/>PG</i></b> | <b><i>Cable<br/>dia. mm</i></b> | <b><i>GL<br/>mm</i></b> | <b><i>H<br/>mm</i></b> |
|-------------------------------|-------------------------|---------------------------------|-------------------------|------------------------|
| 73 04 000 0030                | 7                       | 3 – 6.5                         | 8                       | 20                     |
| 73 04 000 0031                | 7                       | 2 – 5                           | 8                       | 20                     |
| 73 04 000 0032                | 9                       | 4 – 8                           | 8                       | 22                     |
| 73 04 000 0033                | 9                       | 2 – 6                           | 8                       | 22                     |
| 73 04 000 0034                | 11                      | 5 – 10                          | 8                       | 24                     |
| 73 04 000 0035                | 11                      | 3 – 7                           | 8                       | 24                     |
| 73 04 000 0036                | 13.5                    | 6 – 12                          | 9                       | 27                     |
| 73 04 000 0037                | 13.5                    | 5 – 9                           | 9                       | 27                     |
| 73 04 000 0038                | 16                      | 10 – 14                         | 10                      | 28                     |
| 73 04 000 0039                | 16                      | 7 – 12                          | 10                      | 28                     |
| 73 04 000 0040                | 21                      | 13 – 18                         | 11                      | 30                     |
| 73 04 000 0041                | 21                      | 9 – 16                          | 11                      | 30                     |
| 73 04 000 0042                | 29                      | 18 – 25                         | 11                      | 38                     |
| 73 04 000 0043                | 29                      | 13 – 20                         | 11                      | 38                     |
| 73 04 000 0044                | 36                      | 22 – 32                         | 13                      | 45                     |
| 73 04 000 0045                | 36                      | 20 – 26                         | 13                      | 45                     |
| 73 04 000 0046                | 42                      | 32 – 38                         | 13                      | 47                     |
| 73 04 000 0047                | 42                      | 25 – 31                         | 13                      | 47                     |
| 73 04 000 0048                | 48                      | 37 – 44                         | 14                      | 47                     |
| 73 04 000 0049                | 48                      | 29 – 35                         | 14                      | 47                     |
| 73 04 000 0022 black          | 21                      | 9 – 16                          | 11                      | 30                     |

