

P-tec Corp. Tel:(866) 695 4162
 2405 Commerce Circle Tel:(719) 589 3122
 Alamosa CO 81101 Fax:(719) 589 3592
 www.p-tec.net



PL501 Series 5mm LED Single Right Angle Holder

Features

- *Popular Right Angle PCB Indicator
- *Housing Material Black Nylon UL94V-2
- *High Light Output
- *1 Green Led with Color Diffused Lens used
- *Reliable and Rugged
- *RoHS Compliant

Absolute Maximum Ratings at $T_A = 25^\circ\text{C}$

Power Dissipation.....	78mW
Reverse Voltage (<math><100\mu\text{A}</math>).....	5.0V
Max Forward Current.....	30mA
Peak Forward Current (1/10 Duty Cycle, 0.1ms Pulse Width).....	100mA
Operating Temperature Range.....	-25°C to $+85^\circ\text{C}$
Storage Temperature Range.....	-40°C to $+100^\circ\text{C}$
Soldering Temperature (1.6 mm below body).....	260° for 5 seconds

Electrical & Optical Characteristics at $T_A = 25^\circ\text{C}$

Part Number	Emitting Color	Chip Material	Peak Wave Length	Dominant Wave Length	Viewing Angle $2\theta_{1/2}$	Forward Voltage @20mA (V)		Luminous Intensity @20mA (mcd)	
						Typ	Max	Min	Typ
Color Diffused Lens			nm	nm	Deg				
PL501-1G13	Green	GaP	567	572	30°	2.1	2.6	17.0	35.0

All dimensions are in **Millimeters**. Tolerance is $\pm 0.25\text{mm}$ unless otherwise specified.

