



**Product:** [5524UL](#)

Fire Alarm, #22-6c BC, FPLR

### Product Description

Fire Alarm Cable, Riser-FPLR, 6-22 AWG solid bare copper conductors with PVC insulation, PVC jacket with ripcord

### Technical Specifications

#### Product Overview

Suitable Applications:	Fire Alarm, Monitor/Detection, Circuits: Audio, Control, Initiating, Notification
------------------------	---

#### Physical Characteristics (Overall)

##### Conductor

AWG	Stranding	Material	No. of Conductors
22	Solid	BC - Bare Copper	6

Conductor Count:	6
------------------	---

##### Insulation

Material	Nominal Wall Thickness
PP - Polypropylene	0.007 in

##### Color Chart

Number	Color
1	Black
2	Red
3	Brown
4	Blue
5	Orange
6	Yellow

##### Outer Shield

Material
No Shield

##### Outer Jacket

Material	Nominal Diameter	Nominal Wall Thickness	Ripcord
PVC - Polyvinyl Chloride	0.168 in	0.015 in	Yes

#### Construction and Dimensions

##### Cabling

Twists
4.4 twist/ft

#### Electrical Characteristics

##### Conductor DCR

Nominal Conductor DCR
15.7 Ohm/1000ft

## Capacitance

Nom. Capacitance Conductor to Conductor
18.5 pF/ft

## Current

Max. Recommended Current [A]
2 Amps per Conductor at 25°C

## Voltage

UL Voltage Rating
300 V RMS

## Temperature Range

UL Temp Rating:	75°C
Operating Temperature Range:	-20°C To +75°C

## Mechanical Characteristics

Bulk Cable Weight:	20.7 lbs/1000ft
Max. Pull Tension:	46.8 lbs
Min. Bend Radius/Minor Axis:	1.5 in

## Standards

NEC Articles:	Article 760
NEC/(UL) Compliance:	FPLR
Other Specification:	California State Fire Marshal

## Applicable Environmental and Other Programs

EU Directive 2000/53/EC (ELV):	Yes
EU Directive 2003/96/EC (BFR):	Yes
EU Directive 2011/65/EU (RoHS 2):	Yes
EU Directive 2012/19/EU (WEEE):	Yes
EU Directive Compliance:	EU Directive 2003/11/EC (BFR)
EU CE Mark:	Yes
MII Order #39 (China RoHS):	Yes

## Flammability, LSOH, Toxicity Testing

UL Flammability:	UL1666 Riser
CSA Flammability:	FT4
UL voltage rating:	300 V RMS

## Plenum/Non-Plenum

Plenum (Y/N):	No
Plenum Number:	6524UL

## Related Part Numbers

### Variants

Item #	Color	UPC
5524UL 002U1000	Red	612825164203

## History

Update and Revision:	Revision Number: 0.302 Revision Date: 05-05-2023
----------------------	--

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product

Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.