## **Data sheet** 2768.2 AQI 3/150 YE





External insulated cross-connector, No. of poles: 3, Mounting type: Plug in, Width: 87.9 mm, Rated current: 309 A; Colour: Yellow

**RAL:** 1026

### **Business data**

Dusiness data	
Article number	2768.2
Article name	AQI 3/150 YE
GTIN (EAN)	4044211054984
Packaging unit	5
Quantity unit	PC
Weight per piece (not including packaging)	243.4 g
Weight per piece (including packaging)	244.8 g
Unit of weight	G
Customs number	85389099
Country of origin	DE
Prio-Article	2768.2
Product description	External insulated cross-connector

## **Data sheet**





87.9 mm	
31 mm	
1000 V	
1000 V	
309 A	
3	
3	
Copper	
Tin-plated	
Polyamide 6.6	
V-2	
-40 °C	
105 °C	
Plug in	
✓	
✓	
3	
Yes	
No	
Yes	
	31 mm  1000 V  1000 V  309 A  3  Copper Tin-plated Polyamide 6.6 V-2 -40 °C 105 °C  Plug in V V 3  Yes No

# **Data sheet** 2768.2 AQI 3/150 YE



Media

## **Data sheet**

## 2768.2 AQI 3/150 YE



### **Accessories**

#### ##INVERSE##CONTA-CONNECT



Feed-through terminal to mounting surface, Screw connection, Mounting type: Mounting surface, Rated cross-section: 150 mm², Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1584.2	RK 150-D BG	4044211047740	5



Ex feed-through terminal ATEX-certified, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 150 mm², Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1477.2	RK 150 Ex BG	4044211107864	5



Feed-through terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 150 mm², Width: 31 mm, Colour: Beige

Article number	Article name	GTIN (EAN)	Packaging unit
1124.2	RK 150 BG	4044211019198	5