

BL2 BPC 1541E-8/128-W10 - Box PC



1272687

<https://www.phoenixcontact.com/us/products/1272687>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



IP30-rated fanless industrial box PC (BPC) with energy-efficient Intel® Atom® E3940 processor with 128 GB eMMC and Windows 10 Enterprise 2019 LTSC operating system.

Commercial data

Item number	1272687
Packing unit	1 pc
Sales key	DR12
Product key	DRBABA
GTIN	4063151465001
Weight per piece (including packing)	920 g
Weight per piece (excluding packing)	746 g
Customs tariff number	84715000
Country of origin	TW

Technical data

Product properties

Product type	Box PC
--------------	--------

Computer data

Processor	Intel® Atom™ E3940 1.6 GHz
Operating system	Windows® 10 IoT Enterprise LTSC 2019 (64-bit), Multi-language
Cooling	passive
RAM	8 GB LPDDR4
Data storage system	M.2 SSD, 128 GB

Display

Display type	none
--------------	------

System properties

User software	without user software
---------------	-----------------------

Electrical properties

Maximum power dissipation for nominal condition	16.8 W
---	--------

Supply

Supply voltage (DC)	24 V DC (CE rating)
Supply voltage range	12 V DC ... 30 V DC (Labeled operational voltage is 12 ... 30 V DC)
Max. current consumption	0.7 A (24 V DC)
Typical current consumption	0.53 A (24 V DC)

Connection data

Screw connection

Connection method	Screw connection
Conductor cross section, rigid	0.2 mm² ... 2.5 mm²
Conductor cross section, flexible	0.2 mm² ... 2.5 mm²
Conductor cross section AWG	25 ... 14

Interfaces

Interfaces	1x DP++
	2x USB 3.0
	2x COM ports
Network	2x Ethernet (10/100/1000 Mbps), RJ45
LAN chipset	Intel® I210-AT

Dimensions

External dimensions

Width / Height / Depth	99 mm / 92 mm / 63 mm
------------------------	-----------------------

1272687

<https://www.phoenixcontact.com/us/products/1272687>

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP30
	IP30
Ambient temperature (operation)	-20 °C ... 60 °C (with 0.5 m/s airflow)
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Permissible humidity (operation)	5 % ... 85 % (non-condensing)
Shock	15g, 11 ms in accordance with IEC 60068-2-27
Vibration (operation)	1g, according to EN 60068-2-6

Approvals

Conformity/Approvals

Conformance	CE-compliant
FCC	Title 47 Part 15 Subpart B:2018 Class A

Mounting

Mounting type	DIN rail mounting
	Wall mounting (Accessories required)

BL2 BPC 1541E-8/128-W10 - Box PC



1272687

<https://www.phoenixcontact.com/us/products/1272687>

Approvals

🔗 To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/1272687>



EAC

Approval ID: RU C-DE.A*08.B01708



EAC-RoHS

Approval ID: RU*-DE*HB.B.00386/20

1272687

<https://www.phoenixcontact.com/us/products/1272687>

Classifications

ECLASS

ECLASS-11.0	19200102
ECLASS-12.0	19200102
ECLASS-13.0	19200102

ETIM

ETIM 8.0	EC001413
----------	----------

UNSPSC

UNSPSC 21.0	43211500
-------------	----------

BL2 BPC 1541E-8/128-W10 - Box PC



1272687

<https://www.phoenixcontact.com/us/products/1272687>

Environmental product compliance

REACH SVHC

Lead 7439-92-1

BL2 BPC 1541E-8/128-W10 - Box PC



1272687

<https://www.phoenixcontact.com/us/products/1272687>

Accessories

SI-RND-U1A - Data interface

1425185

<https://www.phoenixcontact.com/us/products/1425185>

Service socket with USB A 3.0 (socket/socket), with protective cover



DP TO VGA ADPTR - Adapter

2400173

<https://www.phoenixcontact.com/us/products/2400173>

DisplayPort to VGA video adapter



BL2 BPC 1541E-8/128-W10 - Box PC



1272687

<https://www.phoenixcontact.com/us/products/1272687>

DP TO DVI ADPTR - Adapter

2400174

<https://www.phoenixcontact.com/us/products/2400174>

DisplayPort to DVI-i video adapter



VL 2.0M DP CABLE - Connecting cable

2404774

<https://www.phoenixcontact.com/us/products/2404774>

DisplayPort (DP) cable (2 m) for use with industrial computers



BL2 BPC 1541E-8/128-W10 - Box PC

1272687

<https://www.phoenixcontact.com/us/products/1272687>



BL2 BPC 1500 WALL MOUNT KIT - Mounting kit

1147655

<https://www.phoenixcontact.com/us/products/1147655>

Mounting kit



BL2 BPC 1500 RTC BATTERY - Battery/accumulator

1147739

<https://www.phoenixcontact.com/us/products/1147739>

Replacement battery (BR2030) for BL2 BPC 1500... IPCs



BL2 BPC 1541E-8/128-W10 - Box PC

1272687

<https://www.phoenixcontact.com/us/products/1272687>



BL2 BPC 1500 DIN RAIL KIT - Mounting kit

1147464

<https://www.phoenixcontact.com/us/products/1147464>



DIN rail mounting kit for BL2 BPC 15... products

BL2 BPC 1500 64GB M.2 SSD KIT - Memory

1147738

<https://www.phoenixcontact.com/us/products/1147738>



64 GB M.2 SSD kit for BL2 1500 IPC, heat spreader, bracket, and thermal pads are included

BL2 BPC 1541E-8/128-W10 - Box PC

1272687

<https://www.phoenixcontact.com/us/products/1272687>



BL2 BPC 1500 128GB M.2 SSD KIT - Memory

1147737

<https://www.phoenixcontact.com/us/products/1147737>



128 GB M.2 SSD kit for BL2 1500 IPC, heat spreader, bracket, and thermal pads are included

MC 1,5/ 2-STF-3,5 - PCB connector

1847055

<https://www.phoenixcontact.com/us/products/1847055>



PCB connector, nominal cross section: 1.5 mm², color: green, nominal current: 8 A, rated voltage (III/2): 160 V, contact surface: Tin, contact connection type: Socket, number of potentials: 2, number of rows: 1, number of positions: 2, number of connections: 2, product range: MC 1,5/...-STF, pitch: 3.5 mm, connection method: Screw connection with tension sleeve, screw head form: L Slotted, conductor/PCB connection direction: 0 °, plug-in system: COMBICON MC 1,5, locking: Screw locking mechanism, mounting: Screw flange, type of packaging: packed in cardboard

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com