

Data sheet | Item number: 2002-1892

End and intermediate plate; 1 mm thick; orange

[www.wago.com/2002-1892](http://www.wago.com/2002-1892)



**Data**

**Physical data**

Width	1 mm / 0.039 inches
Height	87.5 mm / 3.445 inches

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Depth	32.9 mm / 1.295 inches
-------	------------------------

**Mechanical Data**

Mounting type	snap-on type
---------------	--------------

**Material Data**

Note (material data)	Information on material specifications can be found here
----------------------	--

Color	orange
Material group	I
Insulation material	Polyamide (PA66)
Flammability class per UL94	V0
Fire load	0.073 MJ
Weight	2.4 g

**Commercial data**

Product Group	22 (TOPJOB S)
eCl@ss 10.0	27-14-11-33
eCl@ss 9.0	27-14-11-33
ETIM 8.0	EC000886
ETIM 7.0	EC000886
PU (SPU)	100 (25) pcs
Packaging type	box
Country of origin	DE
GTIN	4045454371913
Customs tariff number	85389099990

**Environmental Product Compliance**

RoHS Compliance Status	Compliant, No Exemption
------------------------	-------------------------

**Approvals / Certificates****Declarations of conformity and manufacturer's declarations**

Logo	Approval	Additional Approval Text	Certificate name
	<b>ATEX-Attestation of Conformity</b> WAGO GmbH & Co. KG	-	-

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



Railway  
WAGO GmbH & Co. KG

-

Railway  
Ready

#### Approvals for hazardous areas

Logo	Approval	Additional Approval Text	Certificate name
	<b>ATEX</b> KIWA Netherlands B.V.	EN 60079	KIWA 17ATEX0030 U
	<b>CCC</b> CNEX	GB/T 3836.3	2020312313000180 (Ex ec IIC Gc)
	<b>IECEX</b> KIWA Netherlands B.V.	EN 60079	IECEX KIWA 17.0014 U (Ex ec IIC Gc)

#### Required accessories

##### End plate

Through terminal block		
<b>Item no.: 2002-1802</b>	4-conductor through terminal block; 2.5 mm <sup>2</sup> ; with test option; same profile as 4-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; orange	<a href="http://www.wago.com/2002-1802">www.wago.com/2002-1802</a>
<b>Item no.: 2002-1801</b>	4-conductor through terminal block; 2.5 mm <sup>2</sup> ; with test option; same profile as 4-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2002-1801">www.wago.com/2002-1801</a>
<b>Item no.: 2002-1804</b>	4-conductor through terminal block; 2.5 mm <sup>2</sup> ; with test option; for Ex e II and Ex i applications; same profile as 4-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; blue	<a href="http://www.wago.com/2002-1804">www.wago.com/2002-1804</a>
<b>Item no.: 2202-1801</b>	4-conductor through terminal block; with push-button; 2.5 mm <sup>2</sup> ; with test option; same profile as 4-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; gray	<a href="http://www.wago.com/2202-1801">www.wago.com/2202-1801</a>
<b>Item no.: 2202-1802</b>	4-conductor through terminal block; with push-button; 2.5 mm <sup>2</sup> ; with test option; same profile as 4-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; orange	<a href="http://www.wago.com/2202-1802">www.wago.com/2202-1802</a>
<b>Item no.: 2202-1804</b>	4-conductor through terminal block; with push-button; 2.5 mm <sup>2</sup> ; with test option; same profile as 4-conductor disconnect terminal block; side and center marking; for DIN-rail 35 x 15 and 35 x 7.5; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; blue	<a href="http://www.wago.com/2202-1804">www.wago.com/2202-1804</a>
Disconnect terminal block for test and measurement		
<b>Item no.: 2002-1874/401-000</b>	4-conductor disconnect/test terminal block; with mechanical interlock; with test option; orange disconnect link; suitable for Ex i applications; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm <sup>2</sup> ; Push-in CAGE CLAMP®; 2,50 mm <sup>2</sup> ; blue	<a href="http://www.wago.com/2002-1874/401-000">www.wago.com/2002-1874/401-000</a>

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.

**Item no.: 2002-1872/401-000**4-conductor disconnect/test terminal block; with mechanical interlock; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; orange[www.wago.com/2002-1872/401-000](http://www.wago.com/2002-1872/401-000)**Item no.: 2002-1871/401-000**4-conductor disconnect/test terminal block; with mechanical interlock; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; gray[www.wago.com/2002-1871/401-000](http://www.wago.com/2002-1871/401-000)

## Disconnect terminal block

**Item no.: 2002-1871**4-conductor disconnect/test terminal block; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; gray[www.wago.com/2002-1871](http://www.wago.com/2002-1871)**Item no.: 2002-1872**4-conductor disconnect/test terminal block; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; orange[www.wago.com/2002-1872](http://www.wago.com/2002-1872)**Item no.: 2002-1874**4-conductor disconnect/test terminal block; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; blue[www.wago.com/2002-1874](http://www.wago.com/2002-1874)**Item no.: 2202-1871**4-conductor disconnect/test terminal block; with push-button; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; gray[www.wago.com/2202-1871](http://www.wago.com/2202-1871)**Item no.: 2202-1874**4-conductor disconnect/test terminal block; with push-button; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; blue[www.wago.com/2202-1874](http://www.wago.com/2202-1874)**Item no.: 2202-1872**4-conductor disconnect/test terminal block; with push-button; with test option; orange disconnect link; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; orange[www.wago.com/2202-1872](http://www.wago.com/2202-1872)

## Carrier terminal block for modules and plugs

**Item no.: 2002-1861**4-conductor carrier terminal block; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; gray[www.wago.com/2002-1861](http://www.wago.com/2002-1861)**Item no.: 2202-1861**4-conductor carrier terminal block; with push-button; for DIN-rail 35 x 15 and 35 x 7.5; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; gray[www.wago.com/2202-1861](http://www.wago.com/2202-1861)

## Fuse terminal block

**Item no.: 2002-1881**4-conductor fuse terminal block; for mini-automotive blade-style fuses; with test option; without blown fuse indication; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; gray[www.wago.com/2002-1881](http://www.wago.com/2002-1881)**Item no.: 2202-1881**4-conductor fuse terminal block; for mini-automotive blade-style fuses; per DIN 7258-3f, ISO 8820-3; with test option; with push-button; without blown fuse indication; 2.5 mm<sup>2</sup>; Push-in CAGE CLAMP<sup>®</sup>; 2,50 mm<sup>2</sup>; gray[www.wago.com/2202-1881](http://www.wago.com/2202-1881)**Optional accessories****End plate**

## Switching module

**Item no.: 2042-1008**

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Switching module; with changeover rocker switch; Switching voltage: 250 VAC; translucent

[www.wago.com/2042-1008](http://www.wago.com/2042-1008)**Item no.: 2042-1108**

Switching module; with momentary switch; Switching voltage: 250 VAC; translucent

[www.wago.com/2042-1108](http://www.wago.com/2042-1108)

## Solid-state relay module

**Item no.: 2042-7304**

Solid-state relay module; Nominal input voltage: 24 VDC; Limiting continuous current: 0.5 A; Railway; Frequency: 100 kHz; Module width: 15 mm

[www.wago.com/2042-7304](http://www.wago.com/2042-7304)**Item no.: 2042-7504**

Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 0 ... 48 VDC; Limiting continuous current: 4 A; 2-wire connection; Railway; Green status indicator; Module width: 10 mm

[www.wago.com/2042-7504](http://www.wago.com/2042-7504)**Item no.: 2042-7204**

Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 3 ... 60 VDC; Limiting continuous current: 0.1 A; 2-wire connection; Railway; Frequency: 10 kHz; Green status indicator; Module width: 10 mm

[www.wago.com/2042-7204](http://www.wago.com/2042-7204)**Item no.: 2042-7604**

Solid-state relay module; Nominal input voltage: 24 VDC; Output voltage range: 16.8 ... 30 VDC; Limiting continuous current: 5 A; 3-wire connection/high-side switching; Railway; Frequency: 5 kHz; Green status indicator; Module width: 15 mm

[www.wago.com/2042-7604](http://www.wago.com/2042-7604)

## Relay module

**Item no.: 2042-3074**

Relay module; Nominal input voltage: 24 VDC; 3 break contacts and 1 make contact; Limiting continuous current: 5 A; Railway; Green status indicator; Module width: 25 mm

[www.wago.com/2042-3074](http://www.wago.com/2042-3074)**Item no.: 2042-3014**

Relay module; Nominal input voltage: 24 VDC; 2 make contact; Limiting continuous current: 8 A; Railway; Green status indicator; Module width: 20 mm

[www.wago.com/2042-3014](http://www.wago.com/2042-3014)**Item no.: 2042-3034**

Relay module; Nominal input voltage: 24 VDC; 1 changeover contact; Limiting continuous current: 10 A; Railway; Green status indicator; Module width: 15 mm

[www.wago.com/2042-3034](http://www.wago.com/2042-3034)**Item no.: 2042-3044**

Relay module; Nominal input voltage: 24 VDC; 2 changeover contacts; Limiting continuous current: 8 A; Railway; Green status indicator; Module width: 20 mm

[www.wago.com/2042-3044](http://www.wago.com/2042-3044)**Item no.: 2042-3024**

Relay module; Nominal input voltage: 24 VDC; 4 make contacts; Limiting continuous current: 5 A; Railway; Green status indicator; Module width: 25 mm

[www.wago.com/2042-3024](http://www.wago.com/2042-3024)**Item no.: 2042-3064**

Relay module; Nominal input voltage: 24 VDC; 1 break and 1 make contact; Limiting continuous current: 8 A; Railway; Green status indicator; Module width: 20 mm

[www.wago.com/2042-3064](http://www.wago.com/2042-3064)**Item no.: 2042-3084**

Relay module; Nominal input voltage: 24 VDC; 2 break and 2 make contacts; Limiting continuous current: 5 A; Railway; Green status indicator; Module width: 25 mm

[www.wago.com/2042-3084](http://www.wago.com/2042-3084)**Item no.: 2042-3819**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 2 make contact; Limiting continuous current: 5 A; Green status indicator; Module width: 20 mm

[www.wago.com/2042-3819](http://www.wago.com/2042-3819)**Item no.: 2042-3829**

Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 4 make contacts; Limiting continuous current: 3 A; Green status indicator; Module width: 25 mm

[www.wago.com/2042-3829](http://www.wago.com/2042-3829)

Subject to changes. Please also observe the further product documentation!

WAGO GmbH &amp; Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



<b>Item no.: 2042-3869</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 break and 1 make contact; Limiting continuous current: 5 A; Green status indicator; Module width: 20 mm	<a href="http://www.wago.com/2042-3869">www.wago.com/2042-3869</a>
<b>Item no.: 2042-3889</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 2 break and 2 make contacts; Limiting continuous current: 3 A; Green status indicator; Module width: 25 mm	<a href="http://www.wago.com/2042-3889">www.wago.com/2042-3889</a>
<b>Item no.: 2042-3849</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 2 changeover contacts; Limiting continuous current: 5 A; Green status indicator; Module width: 20 mm	<a href="http://www.wago.com/2042-3849">www.wago.com/2042-3849</a>
<b>Item no.: 2042-3879</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 3 break contacts and 1 make contact; Limiting continuous current: 3 A; Green status indicator; Module width: 25 mm	<a href="http://www.wago.com/2042-3879">www.wago.com/2042-3879</a>
<b>Item no.: 2042-3839</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 changeover contact; Limiting continuous current: 4 A; Green status indicator; Module width: 15 mm	<a href="http://www.wago.com/2042-3839">www.wago.com/2042-3839</a>
<b>Item no.: 2042-3054</b> Relay module; Nominal input voltage: 24 VDC; 1 break contact; Limiting continuous current: 6 A; Railway; Green status indicator; Module width: 10 mm	<a href="http://www.wago.com/2042-3054">www.wago.com/2042-3054</a>
<b>Item no.: 2042-3004</b> Relay module; Nominal input voltage: 24 VDC; 1 make contact; Limiting continuous current: 6 A; Railway; Green status indicator; Module width: 10 mm	<a href="http://www.wago.com/2042-3004">www.wago.com/2042-3004</a>
<b>Item no.: 2042-3809</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 make contact; Limiting continuous current: 3 A; Green status indicator; Module width: 10 mm	<a href="http://www.wago.com/2042-3809">www.wago.com/2042-3809</a>
<b>Item no.: 2042-3859</b> Relay module; Nominal input voltage: 24 ... 230 V AC/DC; 1 break contact; Limiting continuous current: 6 A; Green status indicator; Module width: 10 mm	<a href="http://www.wago.com/2042-3859">www.wago.com/2042-3859</a>

## Downloads

### Documentation

#### Bid Text

2002-1892 X81 - Datei	2019 年2月19 日	xml 2.6 kB	Download
2002-1892 doc - Datei	2017 年4月27 日	doc 24.1 kB	Download

#### Additional Information

pdf  
2.2 MB  
Download

Subject to changes. Please also observe the further product documentation!

WAGO GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



## CAD/CAE-Data

### CAD data

2D/3D Models 2002-1892	<a href="#">URL</a>	<a href="#">Download</a>
------------------------	---------------------	--------------------------

### CAE data

EPLAN Data Portal 2002-1892	<a href="#">URL</a>	<a href="#">Download</a>
-----------------------------	---------------------	--------------------------

WSCAD Universe 2002-1892	<a href="#">URL</a>	<a href="#">Download</a>
--------------------------	---------------------	--------------------------

ZUKEN Portal 2002-1892	<a href="#">URL</a>	<a href="#">Download</a>
------------------------	---------------------	--------------------------

## Environmental Product Compliance

### Compliance Search

Environmental Product Compliance 2002-1892 End and intermediate plate; 1 mm thick; orange	<a href="#">URL</a>	<a href="#">Download</a>
--	---------------------	--------------------------

## Installation Notes

### Product family

#### TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!